

Product Information

BRAKE FLUID

Description

Morris Brake Fluid is made from high molecular weight polyalkylene glycol ethers and polyalkylene glycol ether borates, to give a high boiling point fluid of DOT 4 quality. The product is blended with special additives that prevent fluid oxidation, rust and the swelling of the piston seals used in conventional brake systems. Morris Brake Fluid has been manufactured to exceed vehicle manufacturer's standards and has been designed for use at high temperatures under the most severe conditions. This fluid is compatible with all other non-mineral brake fluids manufactured to the same specifications.

Applications

Morris Brake Fluid is suitable for use in all brake and clutch systems where a non-mineral oil grade has been specified meeting the performance levels listed below. Always check manufacturer's handbooks for the correct fluid type as mis-application will impair brake operation and pose a threat to vehicle safety.

Performance Levels

Morris Brake Fluid is designed to exceed the following specifications.

U.S. Federal Motor Vehicle Safety Standard	FMVSS 116 DOT 3 and DOT 4
U.S. Society of Automotive Engineers	SAE J 1703
International Standards Organisation	ISO 4925
Japanese Industrial Standards	JIS K 2233

General Properties

Boiling Point °C	230 min
Viscosity at 100°C, cSt.	2.8
Viscosity at -40°C, cSt.	1425
Flash Point (Open) °C	140
Low Temperature Fluidity °C	-50



Certificate No. FM 21756
BS EN ISO9001 2000

Morris Lubricants, Castle Foregate, Shrewsbury, Shropshire SY1 2EL

Telephone (01743) 232200 Fax (01743) 353584



Certificate No. EMS 60044
BS EN ISO14001 1996