

Product Information

K62 BENTONITE GREASE

Description

K62 is a premium quality non-melting grease for use in plain and anti-friction bearings subjected to elevated temperatures. The consistency of the grease remains stable throughout a wide temperature range.

FEATURES

- High degree of water resistance.
- Good pumpability characteristics.
- Good sealing properties in dusty conditions.
- Wide temperature range.

Applications

K62 is recommended for use in all industrial ball, roller and plain bearings where extremely high temperatures are coupled with heavy loads. K62 can be used at temperatures from -20 to 160°C. The grease is particularly useful in applications where melting out or dripping of grease would cause damage to production or materials, and therefore is highly recommended for overhead conveyor bearings in high temperature environments.

As with all greases used for the first time, check compatibility with the grease applied previously and if necessary purge bearings prior to application. Likewise, as a general rule, take care not to over-lubricate and apply the quantity of grease recommended by the bearing manufacturer.

Not recommended for automotive use. Do not mix with non-bentone greases.

Physical Characteristics

Appearance	Smooth grease
NLGI consistency	2
Thickener	Bentone
Base oil viscosity @ 40 °C (IP71) cSt	110



Certificate No. FM 21756
BS EN ISO9001 2000

Morris Lubricants, Castle Foregate, Shrewsbury, Shropshire SY1 2EL

Telephone (01743) 232200 Fax (01743) 353584



Certificate No. EMS 60044
BS EN ISO14001 1996

