



Liquimatic No. 2

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2020/878.
SDS Reference Number: 21465
Issue date: 17/10/2023 Revision date: 20/02/2026 Supersedes version of: 20/06/2024 Version: 1.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Liquimatic No. 2
Product code : 7060
Type of product : Hydraulic oil
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category : Industrial use, Professional use
Use of the substance/mixture : Lubricants and additives
Function or use category : Lubricants and additives

Title	Life cycle stage	Use descriptors
General industrial use of lubricants and greases in vehicles or machinery. Includes filling and draining of containers and enclosed machinery (including engines)	Professional, Consumer	SU3, PC17, PC24, PROC1, PROC8b, ERC4, ERC7

Full text of use descriptors: see section 16

1.3. Details of the supplier of the safety data sheet

Manufacturer

Morris Lubricants
Castle Foregate
SY1 2EL Shrewsbury, Shropshire
United Kingdom
T +44 (0) 1743 232200
sds@morris-lubricants.co.uk

1.4. Emergency telephone number

Emergency number : +44 (0) 1743 232200
08.45 - 17.00 GMT

Country/Area	Organisation	Emergency number
United Kingdom	NHS 111/NHS 24/NHS Direct.	111 0845 4647 or call a doctor

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aspiration hazard, Category 1 H304
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

Liquimatic No. 2

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2020/878.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS08

Signal word (CLP) :

Danger

Contains :

Lubricating Oil (Petroleum) C15-30 hydrotreated neutral oil-based; Distillates (petroleum), hydrotreated heavy paraffinic

Hazard statements (CLP) :

H304 - May be fatal if swallowed and enters airways.

Precautionary statements (CLP) :

P301+P310 - IF SWALLOWED: Immediately call a doctor, a POISON CENTRE.

P331 - Do NOT induce vomiting.

P405 - Store locked up.

P501 - Dispose of contents and container to a hazardous or special waste collection point.

EUH-statements :

EUH208 - Contains N,N-bis(2-ETHYLHEXYL)-((1,2,4-TRIAZOL-1-YL)METHYL)AMINE, Maleic Anhydride. May produce an allergic reaction.

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated heavy paraffinic	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627-25, UK-01-1759217276-5	$\geq 50 - < 70$	Asp. Tox. 1, H304
Lubricating Oil (Petroleum) C15-30 hydrotreated neutral oil-based	CAS-No.: 72623-86-0 EC-No.: 276-737-9 EC Index-No.: 649-482-00-X REACH-no: UK-01-6260983107-X-XXXX, 01-2119474878-16	$\geq 30 - < 50$	Asp. Tox. 1, H304
Highly refined mineral oil (C15 - C50) substance with national workplace exposure limit(s) (BE, BG, CZ, DK, FI, GB, GR, HU, IE, LT, LV, NL, PL, PT, RO, SE, SK, IS, NO, CH)	-	< 1	Not classified
Hydrocarbons, C16-C20, n-alkanes, isoalkanes, cyclics, <2% aromatics substance with national workplace exposure limit(s) (NO)	CAS-No.: 64742-46-7 EC-No.: 265-148-2 EC Index-No.: 649-221-00-X REACH-no: 01-2119826592-36	< 0.1	Asp. Tox. 1, H304

Liquimatic No. 2

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2020/878.

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
N,N-bis(2-ETHYLHEXYL)-((1,2,4-TRIAZOL-1-YL)METHYL)AMINE	CAS-No.: 91273-04-0 EC-No.: 401-280-0 EC Index-No.: 613-072-00-9 REACH-no: 01-0000015116-78, 01-2119930450-49, UK-01-1625361544-3	< 0.1	Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Chronic 1, H410
Diphenylamine substance with national workplace exposure limit(s) (GB, NO)	CAS-No.: 122-39-4 EC-No.: 204-539-4 EC Index-No.: 612-026-00-5 REACH-no: 01-2119488966-13	< 0.1	Acute Tox. 3 (Inhalation), H331 (ATE=0.5 mg/l/4h) Acute Tox. 3 (Dermal), H311 (ATE=300 mg/kg bodyweight) Acute Tox. 3 (Oral), H301 (ATE=100 mg/kg bodyweight) STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Maleic Anhydride substance with national workplace exposure limit(s) (GB, NO)	CAS-No.: 108-31-6 EC-No.: 203-571-6 EC Index-No.: 607-096-00-9 REACH-no: 01-2119463268-32, UK-01-3403519668-1	< 0.1	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Skin Corr. 1B, H314 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1A, H317 STOT RE 1, H372 EUH071
naphthalene substance with national workplace exposure limit(s) (NO); substance with a Community workplace exposure limit	CAS-No.: 91-20-3 EC-No.: 202-049-5 EC Index-No.: 601-052-00-2 REACH-no: 01-2119561346-37	< 0.1	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Carc. 2, H351 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Specific concentration limits:

Name	Product identifier	Specific concentration limits (%)
Diphenylamine	CAS-No.: 122-39-4 EC-No.: 204-539-4 EC Index-No.: 612-026-00-5 REACH-no: 01-2119488966-13	(10 ≤ C < 100) STOT RE 2; H373
Maleic Anhydride	CAS-No.: 108-31-6 EC-No.: 203-571-6 EC Index-No.: 607-096-00-9 REACH-no: 01-2119463268-32, UK-01-3403519668-1	(0.001 ≤ C ≤ 100) Skin Sens. 1A; H317

Comments

: A petroleum product. DMSO extract < 3 % weight (IP 346)

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

: If you feel unwell, seek medical advice.

First-aid measures after inhalation

: Move the affected person away from the contaminated area and into the fresh air. If you feel unwell, seek medical advice.

Liquimatic No. 2

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2020/878.

First-aid measures after skin contact	: Take off contaminated clothing and wash it before reuse. Gently wash with plenty of soap and water.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Get medical advice/attention if you feel unwell. Do NOT induce vomiting. Aspiration of this material may cause chemical pneumonia.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.
Symptoms/effects after inhalation	: None under normal use. Inhalation may cause irritation (cough, short breathing, difficulty in breathing).
Symptoms/effects after skin contact	: Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: May cause slight irritation.
Symptoms/effects after ingestion	: Aspiration of this material may cause chemical pneumonia.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Dry chemical, CO ₂ , dry sand, or alcohol-resistant foam.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon monoxide. Carbon dioxide.

5.3. Advice for firefighters

Precautionary measures fire	: Keep container closed when not in use.
Firefighting instructions	: Prevent fire fighting water from entering the environment. Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Evacuate unnecessary personnel. Caution : this product can cause the floor to be very slippery.

6.2. Environmental precautions

Do not allow to enter drains or water courses. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up	: Clear up rapidly by scoop or vacuum. Collect leaking and spilled liquid in sealable containers as far as possible. Absorb remaining liquid with sand or inert absorbent and remove to safe place. Notify authorities if product enters sewers or public waters. This material and its container must be disposed of in a safe way, and as per local legislation.

Liquimatic No. 2

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2020/878.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling	: Do not eat, drink or smoke when using this product.
Hygiene measures	: Wear personal protective equipment. Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Store in a well-ventilated place. Keep container tightly closed.
Storage conditions	: Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep container closed when not in use. Store in a dry place.
Incompatible products	: Oxidizing agent. Strong acids. Strong bases.
Storage area	: Store in a well-ventilated place.
Special rules on packaging	: Store in a closed container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

Highly refined mineral oil (C15 - C50)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	5 mg/m ³
WEL STEL (OEL STEL)	10 mg/m ³
Regulatory reference	EU OEL
Diphenylamine (122-39-4)	
United Kingdom - Occupational Exposure Limits	
Local name	Diphenylamine
WEL TWA (OEL TWA)	10 mg/m ³
WEL STEL (OEL STEL)	20 mg/m ³
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Maleic Anhydride (108-31-6)	
United Kingdom - Occupational Exposure Limits	
Local name	Maleic anhydride
WEL TWA (OEL TWA)	1 mg/m ³
WEL STEL (OEL STEL)	3 mg/m ³
Remark	Sen (Capable of causing occupational asthma)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Liquimatic No. 2

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2020/878.

naphthalene (91-20-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Naphthalene
IOEL TWA	50 mg/m ³
	10 ppm
Remark	(Year of adoption 2010)
Regulatory reference	COMMISSION DIRECTIVE 91/322/EEC; SCOEL Recommendations

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Personal protection equipment

Personal protective equipment symbol(s):



Eye and face protection

Eye protection:

Chemical goggles or face shield

Skin protection

Skin and body protection:

Wear protective clothing

Respiratory protection

Respiratory protection:

No respiratory protection needed under normal use conditions

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: amber.
Appearance	: Liquid.
Odour	: mild.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: > 320 °C
Flammability	: Not flammable, Heating may cause a fire.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 170 °C PMCC
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic @ 40°C	: 14.68 mm ² /s
Solubility	: Material nearly insoluble in water. Soluble in organic solvents.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available

Liquimatic No. 2

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2020/878.

Density	: Not available
Relative density	: 0.855
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

Other safety characteristics

Additional information : The product is a complex mixture, the majority of which would not be classed as a VOC. However it cannot be discounted that trace or low levels of VOCs may be present.

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Extremely high or low temperatures. Moisture.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Hydrocarbons, C16-C20, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-46-7)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

N,N-bis(2-ETHYLHEXYL)-((1,2,4-TRIAZOL-1-YL)METHYL)AMINE (91273-04-0)

LD50 oral rat	> 2000 mg/kg ECHA
LD50 oral	2356 mg/kg bodyweight
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

Maleic Anhydride (108-31-6)

LD50 dermal rabbit	2620 mg/kg bodyweight Animal: rabbit, Animal sex: female, OECD Guideline 402 (Acute Dermal Toxicity)
--------------------	--

Skin corrosion/irritation : Not classified (Based on available data, the classification criteria are not met)

Liquimatic No. 2

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2020/878.

Additional information	: Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met)
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified
Additional information	: This product contains mineral oils which are considered to be severely refined and not considered to be carcinogenic under IARC. All of the oils in this product have been demonstrated to contain less than 3% extractables by the IP346 test
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)

N,N-bis(2-ETHYLHEXYL)-((1,2,4-TRIAZOL-1-YL)METHYL)AMINE (91273-04-0)

NOAEL (animal/male, F1)	100 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)

Diphenylamine (122-39-4)

NOAEL (oral, rat, 90 days)	3 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Maleic Anhydride (108-31-6)

NOAEL (oral, rat, 90 days)	≈ 10 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies)
NOAEC (inhalation, rat, vapour, 90 days)	≈ 0.0033 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
STOT-repeated exposure	Causes damage to organs (respiratory system) through prolonged or repeated exposure (inhalation).

Aspiration hazard : May be fatal if swallowed and enters airways.

Liquimatic No. 2

Viscosity, kinematic @ 40°C	14.68 mm ² /s
-----------------------------	--------------------------

Lubricating Oil (Petroleum) C15-30 hydrotreated neutral oil-based (72623-86-0)

Viscosity, kinematic @ 40°C	7.5 mm ² /s
-----------------------------	------------------------

Hydrocarbons, C16-C20, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-46-7)

Viscosity, kinematic @ 40°C	19 mm ² /s
-----------------------------	-----------------------

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified
Additional information	: Based on available data, the classification criteria are not met.

N,N-bis(2-ETHYLHEXYL)-((1,2,4-TRIAZOL-1-YL)METHYL)AMINE (91273-04-0)

LC50 - Fish [1]	1.1 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	2.2 mg/l Test organisms (species): Daphnia magna

Liquimatic No. 2

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2020/878.

N,N-bis(2-ETHYLHEXYL)-((1,2,4-TRIAZOL-1-YL)METHYL)AMINE (91273-04-0)	
EC50 72h - Algae [1]	0.66 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	> 0.96 mg/l Desmodesmus subspicatus (Scenedesmus subspicatus)
ErC50 algae	> 0.96 mg/l (BASF)
NOEC chronic fish	> 100 mg/l Test organisms (species): Duration: '28 d'

Diphenylamine (122-39-4)	
EC50 - Crustacea [1]	2 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	2.17 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

Maleic Anhydride (108-31-6)	
LC50 - Fish [1]	75 mg/l Oncorhynchus mykiss
LC50 - Fish [2]	75 mg/l Lepomis macrochirus
EC50 - Crustacea [1]	330 mg/l Daphnia magna
EC50 72h - Algae [1]	> 150 mg/l Pseudokirchneriella subcapitata

12.2. Persistence and degradability

Liquimatic No. 2	
Persistence and degradability	Not established.

Lubricating Oil (Petroleum) C15-30 hydrotreated neutral oil-based (72623-86-0)	
Persistence and degradability	Not rapidly degradable

Hydrocarbons, C16-C20, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-46-7)	
Persistence and degradability	Not rapidly degradable

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Persistence and degradability	Not rapidly degradable

Highly refined mineral oil (C15 - C50)	
Persistence and degradability	Not rapidly degradable

N,N-bis(2-ETHYLHEXYL)-((1,2,4-TRIAZOL-1-YL)METHYL)AMINE (91273-04-0)	
Persistence and degradability	Not rapidly degradable

Diphenylamine (122-39-4)	
Persistence and degradability	Not rapidly degradable

Maleic Anhydride (108-31-6)	
Persistence and degradability	Not rapidly degradable

naphthalene (91-20-3)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

Liquimatic No. 2

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2020/878.

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose of contents/container to a hazardous or special waste collection point.
European List of Waste (LoW, EC 2000/532) : 13 02 04* - mineral-based chlorinated engine, gear and lubricating oils
15 01 10* - packaging containing residues of or contaminated by dangerous substances
HP Code : HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not regulated for transport				
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

Inland waterway transport

Not regulated

Rail transport

Not regulated

Liquimatic No. 2

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2020/878.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals): Diphenylamine (122-39-4)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Not listed on the Ozone Depletion list (Regulation EU 2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

CAS-No.	Chemical Abstracts Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DNEL	Derived-No Effect Level
EC-No.	European Community number
ED	Endocrine disruptor
IARC	International Agency for Research on Cancer

Liquimatic No. 2

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2020/878.

Abbreviations and acronyms:	
LC50	Median lethal concentration
LD50	Median lethal dose
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
SDS	Safety Data Sheet
STP	Sewage treatment plant
VOC	Volatile Organic Compounds
WGK	Water Hazard Class
vPvB	Very Persistent and Very Bioaccumulative

Data sources	: ECHA (European Chemicals Agency). REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006. Supplier's safety documents.
Training advice	: Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H- and EUH-statements:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Resp. Sens. 1	Respiratory sensitisation, Category 1
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Sens. 1A	Skin sensitisation, category 1A
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.

Liquimatic No. 2

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2020/878.

Full text of H- and EUH-statements:	
H331	Toxic if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.
EUH208	Contains N,N-bis(2-ETHYLHEXYL)-((1,2,4-TRIAZOL-1-YL)METHYL)AMINE, Maleic Anhydride. May produce an allergic reaction.

Full text of use descriptors	
ERC4	Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
ERC7	Use of functional fluid at industrial site
PC17	Hydraulic Fluids
PC24	Lubricants, greases, release products
PROC1	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
PROC8b	Transfer of substance or mixture (charging and discharging) at dedicated facilities
SU3	Industrial uses: Uses of substances as such or in preparations at industrial sites

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.