



Product Information:

AGRIMAX® UTTO 10W-40 PLANT AND FARM OIL

Description:

Agrimax® UTTO 10W-40 offers versatility, performance and grade rationalisation opportunities in one product formulation. Product chemistry has been optimised for use in final drives, hydraulics, wet brakes and transmissions and will help to maintain component integrity and operational efficiency.

Benefits:

- Single oil avoiding and reducing inventory costs
- OEM approved – assured performance
- Prolongs hardware and component longevity
- Outstanding wear, rust and corrosion protection
- Balanced friction performance give precise clutch and brake operation

Applications:

May be used in a wide variety of applications, including:

- Tractors
- Combine harvesters
- Crop sprays and other ancillary equipment
- Certain makes/models of construction equipment
- Materials handling equipment

Performance Levels:

MF M-1145 Approved
MF M-1144 / M-1139
Ford M2C-159B / M2C-121B
John Deere JDM J27
ZF TE-ML 06B (includes C,Q,R)
ZF TE-ML 06D, 06F, 07B
API GL-4
Allison C4
Caterpillar T0-2

Physical Characteristics:

SAE Grade	10W-40
Density at 15 °C	0.866
Viscosity cSt at 100 °C	12.54
Viscosity cSt at 40 °C	80.74
Viscosity Index	154
Flash Point (closed) °C	162
Pour Point °C	-37
TBN	11.50

Figures based on average production values.

Part no.s: SVT025, SVT205

(TDS Agrimax® UTTO 10W-40– 110122 Issue 7)

