

Product Information:
MULTIVIS CST ME
10W-30 & 15W-40



Description

Multivis CST ME 10W-30 and 15W-40 are engine oils manufactured from high quality mineral oils and a high performance additive system. These grades have been optimised for use in petrol engines, naturally aspirated and turbocharged versions.

Multivis CST ME 10W-30 and 15W-40 engine oils provide a high level of engine cleanliness and control the formation of high temperature lacquers and low temperature sludges. Powerful anti-wear technology ensures maximum component life, together with protection from oxidation, rust and corrosion.

Key Features

- Outstanding Soot Handling
- Enhanced Sludge Dispersancy
- High levels of Piston Cleanliness
- Improved Anti-wear protection

Applications

Multivis CST ME 10W-30 and 15W-40 are engine oils are suitable for use in passenger cars, light commercial vehicles, etc. where an oil of this type and specification is required.

Performance Levels

API SM/SN/CF

Physical Characteristics:

| | | |
|-------------------------|--------------|--------------|
| SAE Classification | 10W-30 | 15W-40 |
| Appearance | Amber liquid | Amber liquid |
| Density @ 15°C | 0.870 | 0.875 |
| Viscosity @ 40°C (cSt) | 65.9 | 103.6 |
| Viscosity @ 100°C (cSt) | 9.9 | 13.5 |
| Viscosity Index | 130 | 130 |
| CCS (mPas) | 5700 @ -25°C | 6300 @ -20°C |
| Closed Flash Point (°C) | 210 | 220 |
| Pour Point (°C) | -39 | -30 |
| Base Number (mg/KOH/g) | 7.4 | 7.4 |

Figures based on average production values

(TDS Multivis CCST ME 10W-30 / 15W-40 range – 081216 Issue 1)

