

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Airforce 4000 ISO VG 68

Product number 7083

Internal identification GHS21477

EU REACH registration

number

n/a Mixture

EU REACH registration notes Due to the transition process from EU to UK REACH, our SDS no longer show EU REACH

numbers on English SDS as they do not apply to the UK market. UK REACH numbers will be shown as they become available from our suppliers. This product is formulated in compliance

with both EU and UK REACH

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Air compressor oil

Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier Morris Lubricants

Castle Foregate Shrewsbury Shropshire SY1 2EL

+44 (0) 1743 232200 +44 (0) 1743 353584

sds@morris-lubricants.co.uk

1.4. Emergency telephone number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Not Classified

2.2. Label elements

Hazard statements NC Not Classified

Precautionary statements P501a Dispose of container/contents to a hazardous or special waste collection point.

Supplemental label

information

EUH210 Safety data sheet available on request.

2.3. Other hazards

Airforce 4000 ISO VG 68

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT) at >0.1%. This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB) at > 0.1%.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Distillates, hydrotreated heavy paraffinic

30-60%

CAS number: 64742-54-7 EC number: 265-157-1 UK REACH registration number: UK-01-

1759217276-5-XXXX

Classification Classification (67/548/EEC or 1999/45/EC)

Not Classified -

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition commentsOther ingredients are below the reporting thresholds

A petroleum product. DMSO extract < 3 % weight (IP 346)

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Get medical attention if any discomfort continues.

Inhalation If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and

keep warm and at rest in a position comfortable for breathing. Get medical attention if any

discomfort continues.

Ingestion Get medical attention if any discomfort continues. Do not induce vomiting.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water.

Eye contact Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do.

Continue rinsing. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation Upper respiratory irritation.

Ingestion The product contains mineral oil, which if aspirated into the lungs through vomiting after

ingestion, may result in chemical pneumonia.

Skin contact Prolonged contact may cause redness, irritation and dry skin.

Eye contact Irritation of eyes and mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing

Do not use water jet as an extinguisher, as this will spread the fire.

media

5.2. Special hazards arising from the substance or mixture

Specific hazards Heat from fire could result in drums bursting

Airforce 4000 ISO VG 68

Hazardous combustion

Protection against nuisance dust must be used when the airborne concentration exceeds 10

mg/m³. Oxides of carbon. Oxides of nitrogen.

5.3. Advice for firefighters

Protective actions during

firefighting

products

Control run-off water by containing and keeping it out of sewers and watercourses.

Special protective equipment

for firefighters

Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions For personal protection, see Section 8. Take care as floors and other surfaces may become

slippery. Keep unnecessary and unprotected personnel away from the spillage.

6.2. Environmental precautions

Environmental precautions The product is insoluble in water and will spread on the water surface. Avoid the spillage or

runoff entering drains, sewers or watercourses. Contain spillage with sand, earth or other

suitable non-combustible material.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up In case of spillage on water prevent the spread by use of suitable barrier equipment Contain

and absorb spillage with sand, earth or other non-combustible material. Collect and place in suitable waste disposal containers and seal securely. Residues and empty containers should

be taken care of as hazardous waste according to local and national provisions.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health

hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

Storage class Miscellaneous hazardous material storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Distillates, hydrotreated heavy paraffinic

Long-term exposure limit (8-hour TWA): ACGIH 5 mg/m³ Short-term exposure limit (15-minute): ACGIH 10 mg/m³

ACGIH = American Conference of Governmental Industrial Hygienists.

Alkyl thiophosphate ester

DNEL Workers - Inhalation; Long term systemic effects: 2.3 mg/m³

Airforce 4000 ISO VG 68

PNEC - Fresh water; 0.038 mg/l

marine water; 0.0038 mg/l
Intermittent release; 0.38 mg/l
Sediment (Freshwater); 12.1 mg/kg
Sediment (Marinewater); 1.21 mg/kg

8.2. Exposure controls

Protective equipment





Appropriate engineering

controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure

limits for the product or ingredients.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates

eye contact is possible. The following protection should be worn: Chemical splash goggles or

face shield.

Hand protection The most suitable glove should be chosen in consultation with the glove

supplier/manufacturer, who can provide information about the breakthrough time of the glove

material.

Hygiene measures

Use engineering controls to reduce air contamination to permissible exposure level. Wash

promptly with soap and water if skin becomes contaminated.

Respiratory protection No specific recommendations. Respiratory protection must be used if the airborne

contamination exceeds the recommended occupational exposure limit.

Thermal hazards Not anticipated under normal conditions of use. The product is combustible if heated

excessively and an ignition source is applied.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Liquid.

Colour Amber.

Odour Oil-like.

Odour threshold Not known.

Melting point -27°C Pour point

Initial boiling point and range >320°C @ 101.3 kPa

Flash point 218°C Pensky-Martens closed cup.

Evaporation rate Not relevant.

Upper/lower flammability or

explosive limits

Not known.

Other flammability Product is not flammable but on excessive heating may become combustible.

Relative density 0.870 @ 15.6°C

Solubility(ies) Insoluble in water. Soluble in the following materials: Organic solvents.

Partition coefficient Not determined. log Kow >7 Typical of mineral oil.

Auto-ignition temperature No specific test data are available.

Airforce 4000 ISO VG 68

Decomposition Temperature Not determined.

Viscosity 67 cSt @ 40°C

Explosive properties Not considered to be explosive.

Explosive under the influence

of a flame

Not considered to be explosive.

Oxidising properties The mixture itself has not been tested but none of the ingredient substances meet the criteria

for classification as oxidising.

9.2. Other information

Volatile organic compound The product is a complex mixture, the majority of which would not be classed as a VOC.

However it cannot be discounted that trace or low levels of VOCs may be present.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Under normal conditions of storage and use, no hazardous reactions will occur.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition

Oxides of carbon. Oxides of nitrogen.

products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD50) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) The product is unlikely to present any significant inhalation hazard at ambient temperatures

and under normal conditions of use.

Serious eye damage/irritation

Serious eye damage/irritation May cause mild, short lasting discomfort to eyes.

Respiratory sensitisation

Respiratory sensitisation Repeated exposure to oil mists may cause respiratory damage. There is no evidence that the

product can cause respiratory hypersensitivity.

Skin sensitisation

Airforce 4000 ISO VG 68

Skin sensitisation Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity This product contains mineral oils which are considered to be severely refined and not

considered to be carcinogenic under IARC. All of the oils in this product have been

demonstrated to contain less than 3% extractables by the IP346 test

Reproductive toxicity

Reproductive toxicity - fertility No data available to suggest the product will cause reproductive toxicity.

Specific target organ toxicity - single exposure

STOT - single exposure Based on available data the classification criteria are not met.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Although not classified, the product contains mineral oil. If aspirated into the lungs e.g.

through vomiting after ingestion, admit to hospital immediately.

General information This product has low toxicity. Only large quantities are likely to have adverse effects on

human health.

Inhalation Unlikely to be hazardous by inhalation because of the low vapour pressure of the product at

ambient temperature.

Ingestion No harmful effects expected from quantities likely to be ingested by accident.

Skin contact Skin irritation should not occur when used as recommended. Repeated exposure may cause

skin dryness or cracking.

Eye contact May cause temporary eye irritation.

Acute and chronic health

hazards

Prolonged or repeated contact with used oil may cause serious skin diseases, such as

dermatitis and skin cancer.

Airforce 4000 ISO VG 68

SECTION 12: Ecological information

Ecotoxicity Based on available data the classification criteria are not met. Not regarded as dangerous for

the environment.

12.1. Toxicity

Toxicity Based on available data the classification criteria are not met. Not considered toxic to fish.

Acute aquatic toxicity

Acute toxicity - aquatic

invertebrates

Based on available data the classification criteria are not met.

12.2. Persistence and degradability

Stability (hydrolysis) The product is based on highly refined mineral oils that are considered stable to hydrolysis.

Biodegradation The product is not considered readily biodegradable, albeit the major constituents are

expected to ultimately biodegrade.

Biological oxygen demand Not determined.

Chemical oxygen demand Not determined.

12.3. Bioaccumulative potential

Bioaccumulative potential Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.

Partition coefficient Not determined. log Kow >7 Typical of mineral oil.

12.4. Mobility in soil

Mobility The product is non-volatile. The product is insoluble in water and will spread on the water

surface.

Henry's law constant Not determined.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substance classified as PBT or vPvB =>0.1%

12.6. Other adverse effects

Other adverse effects None known.

Endocrine Disruption The substance/mixture does not contain components considered to have endocrine disrupting

properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Dispose of waste via a licensed waste disposal contractor.

Waste class European Waste Catalogue (EWC) number = 13 08 99* (waste not otherwise specified)

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

Airforce 4000 ISO VG 68

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations GB CLP Regulation

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 (SI 2020 No. 1577) (as

amended).

Guidance Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Inventories

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

Australia - AIIC

All the ingredients are listed or exempt.

Korea - KECI

All the ingredients are listed or exempt.

China - IECSC

All the ingredients are listed or exempt.

Philippines – PICCS

All the ingredients are listed or exempt.

New Zealand - NZIOC

All the ingredients are listed or exempt.

SECTION 16: Other information

Airforce 4000 ISO VG 68

Abbreviations and acronyms used in the safety data sheet

ADR: European Agreement concerning the International Carriage of Dangerous Goods by

Road.

CAS: Chemical Abstracts Service.

DNEL: Derived No Effect Level.

GHS: Globally Harmonized System.

IATA: International Air Transport Association. IMDG: International Maritime Dangerous Goods.

REACH: The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577.

vPvB: Very Persistent and Very Bioaccumulative.

Classification abbreviations and acronyms

Acute Tox. = Acute toxicity

Aquatic Acute = Hazardous to the aquatic environment (acute)

Aquatic Chronic = Hazardous to the aquatic environment (chronic)

Asp. Tox. = Aspiration hazard Carc. = Carcinogenicity

Eye Dam. = Serious eye damage

Eye Irrit. = Eye irritation
Flam. Gas = Flammable gas
Flam. Liq. = Flammable liquid
Met. Corr. = Corrosive to metals
Repr. = Reproductive toxicity

Resp. Sens. = Respiratory sensitisation

Skin Corr. = Skin corrosion Skin Irrit. = Skin irritation Skin Sens. = Skin sensitisation

STOT RE = Specific target organ toxicity-repeated exposure STOT SE = Specific target organ toxicity-single exposure

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Issued by Regulatory Affairs

Revision date 17/10/2022

Revision 4

Supersedes date 21/01/2020

SDS number 21477

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.