



Product Information:

GROUND FORCE 2T

UNIVERSAL 2-STROKE ENGINE OIL FOR PREMIX & INJECTOR SYSTEMS

Description

Groundforce 2T has been developed to meet the requirements of small high revving air cooled 2-stroke engines in horticultural and agricultural equipment. The lubricating film is strong enough to prevent engine lock up in moments of temporary overheating and provides maximum film strength and anti-wear performance. Reduced smoke and clean burning characteristics mean that deposit formation in the ports and exhaust are virtually eliminated.

Applications

Groundforce 2T is designed for use in the engines of two stroke powered equipment in tool and horticultural hire shops. This includes chain saws, abrasive disc cutters, angle grinders, chippers, shredders, hover mowers, scarifiers, weed cutters, strimmers and hedge cutters.

Always follow engines manufacturers' mixture recommendations.

Performance Levels

API TC+

JASO FB

Physical Characteristics

Appearance	Blue/Green liquid
Density at 15.6 °C	0.850
Kinematic Viscosity @ 100 °C (cSt)	9.9
Kinematic Viscosity @ 40 °C (cSt)	81.8
Viscosity Index	105
Closed Flash Point (°C)	210
Sulphated Ash (%wt)	<0.10

Figures based on average production values.

Part No.s: GTT500, GTT001, GTT005, GTT025, GTT205

(TDS Groundforce 2T – 301025 Issue 6)

