Product Information:





Description

Multivis ADT DV 5W-30 is a synthetic technology engine oil formulated to cope with the exacting demands of OEMs requiring low viscosity engine oils. The product uses a combination of synthetic base fluids and an advanced additive system to provide a balanced lubricant that delivers friction reduction, component protection and fuel efficiency. Multivis ADT DV 5W-30 has been developed to help combat the issue of Low Speed Pre-ignition (LSPI) which can cause damage to certain petrol engine types.

Multivis ADT DV 5W-30 provides the following benefits:

- Contributes to overall fuel efficiency
- Circulates rapidly from cold
- Strong oil film protects at high temperatures and under arduous work loads
- Ensures a high level of component cleanliness and operational efficiency

Applications

Recommended for use in engines where a lubricant of this viscosity and performance level is specified in handbooks, particularly Opel/Vauxhall Group petrol models, 1.4 and 1.0 turbo units, model year 2010 onwards.

Performance Levels

API SP ILSAC GF-5 GM dexos1 Gen 2

Physical Characteristics

Viscosity @ 100°C, cSt.	10.11
Viscosity @ 40°C. cSt.	59.11
Viscosity Index	159
Density @ 15.5°C	0.852
Flash Point (Closed) °C	210
TBN, mg/KOH/g	9.2
Pour Point °C	-42

Figures based on average production values.

Part No.s: ADVI01, ADV205, ADV025, ADV005, ADV001

(TDS Multivis ADT DV 5W-30 – 090320 issue I)









