

## Product Information:

# GEO ULTRA NG 40

## High Performance Gas Engine Oil



### Description:

Morris GEO NG 40 is a premium high performance, low ash gas engine oil primarily formulated to lubricate high-output, 4-cycle natural gas engines operating on natural gas.



Morris GEO NG 40 has been developed and formulated to provide outstanding deposit, wear, oxidation and nitration control. Through a combination of field trials and laboratory testing, exceptional performance has been shown in highly rated gas engines even with sumps sizes < 100 litres.

### Features:

- Proven engine performance fueled by Natural Gas
- Low oil consumption.
- Enhanced corrosion protection.
- Enhanced wear protection.

### Recommendations:

MTU	Proof of performance
GE Jenbacher	
Perkins	
MWM	(TCG 2016, TCG 2020, TCG 2032)
Caterpillar	Proof of performance
Cummins	
Waukesha	Proof of performance

Morris recommendations are derived from engine trials on multiple engines and locations using a variety of gases. The listing is not exhaustive, therefore please contact your local representative for further information on specific models.

### Physical Characteristics:

Density at 15°C (g/cm <sup>3</sup> )	0.872
Viscosity @ 100°C (cSt)	13.9
Viscosity @ 40°C (cSt)	121.5
Viscosity Index	118
Flash Point PMCC (°C)	170
Pour Point (°C)	-18
TBN (mgKOH/g)	6.0
Sulphated Ash (%wt)	0.49%

\*Figures based on average production values

(TDS GEO NG 40 – 020721 Issue 2)

