

Product Information:

MULTIVIS ECO-S 0W-20

SYNTHETIC TECHNOLOGY – FUEL EFFICIENT

Description

Multivis ECO-S 0W-20 is a high performance synthetic technology engine oil formulated to cope with the exacting demands of OEMs requiring low viscosity engine oils. The product uses a combination of synthetic base fluids and an advanced additive system to provide a balanced lubricant that delivers friction reduction, component protection and fuel efficiency.

Multivis ECO-S 0W-20 provides low-speed pre-ignition (LSPI) protection for gasoline direct injection engines and protects catalytic converters from fouling.

Multivis ECO-S 0W-20 provides the following benefits:

- Contributes to overall fuel efficiency
- Circulates rapidly from cold
- Strong oil film protects at high temperatures and under arduous work loads
- Ensures a high level of component cleanliness and operational efficiency

Applications

Recommended for use in engines where a lubricant of this viscosity and performance level is specified in handbooks. Manufacturers include: Honda, Suzuki, Subaru, Toyota, Mazda and Mitsubishi.

Performance Levels

API SP, API SN

API SN Plus, API SN Plus RC

ILSAC GF-6A

GM dexos1™ Gen 2

Physical Characteristics

Viscosity @ 100°C, cSt.	8.23
Viscosity @ 40°C, cSt.	42.34
Viscosity Index	173
Density @ 15.5°C	0.846
Flash Point (Closed) °C	209
TBN, mg/KOH/g	8.5
Pour Point °C	-33

Figures based on average production values.

Part No.s: ECS001, ECS005, ECS025, ECS205

(TDS Multivis ECO-S 0W-20 – 020720 issue 4)

