



Product Information:
ECOTRANS 75W-80
HEAVY DUTY TRANSMISSION OIL

Description

Ecotrans 75W-80 is a synthetic technology, high performance transmission fluid, developed for use in ZF manual and automated manual transmission (AMT) systems. The product not only offers a high level of component protection under a wide range of operating conditions and loads, but improved gear shift and improvements in fuel economy.

Features and Benefits

- Improved gear shift performance
- Protects components under high load conditions
- Improved transmission efficiency with potential fuel savings
- High temperature stability during sustained long distance schedules

Applications

Ecotrans 75W-80 can be used in ZF manual and automated manual transmission (AMT) systems fitted to commercial vehicles, light commercial vehicles, coaches and buses, where one of the specifications below is listed. The versatility of Ecotrans 75W-80 allows it to be used in any other types of transmission system requiring an API GL4 lubricant of this viscosity grade.

Performance Level

API GL-4

Renault (In accordance with Renault Note Technique B0032/2 Annex 3)

MAN 341 Type E3, Z-4

Volvo 97307 (Approved)

ZF TE ML 01L, 02L, 08, 13*,16K, 24A

Can be used in DAF, Eaton (Eaton Europe - 300,000 kms or 3 years) and Iveco transmissions where a product of this type is specified.

*where ZF TE-ML 13 stipulates ZF TE-ML 02L

Physical Characteristics

Viscosity @ 100°C, cSt.	9.38
Viscosity @ 40°C, cSt.	55.58
Viscosity Index	152
Flash Point, Closed (°C)	150
Pour Point (°C)	-33

Figures based on average production values.

Part No.s: ECT025, ECT205

(TDS Ecotrans 75W-80 – 190318 Issue 8)

