



# Liquimatic D46

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Reference number: 21469  
Issue date: 30/03/2023 Revision date: 30/03/2023 Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : Liquimatic D46  
Product code : 7067  
Type of product : Hydraulic oil, Transmission Oil  
Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Professional use  
Use of the substance/mixture : Lubricants and additives  
Function or use category : Lubricants and additives

##### 1.2.2. Uses advised against

Restrictions on use : No specific uses advised against. Use only for the intended applications

#### 1.3. Details of the supplier of the safety data sheet

##### Manufacturer

Morris Lubricants  
Castle Foregate  
SY1 2EL Shrewsbury – Shropshire  
United Kingdom  
T +44 (0) 1743 232200  
[sds@morris-lubricants.co.uk](mailto:sds@morris-lubricants.co.uk)

#### 1.4. Emergency telephone number

Emergency number : +44 (0) 1743 232200  
08.45 - 17.00 GMT

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazardous to the aquatic environment – Chronic Hazard, Category 3 H412  
Full text of H- and EUH-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

No additional information available

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Signal word (CLP) : -  
Hazard statements (CLP) : H412 - Harmful to aquatic life with long lasting effects.  
Precautionary statements (CLP) : P273 - Avoid release to the environment.  
P501 - Dispose of contents and container to a hazardous or special waste collection point.  
EUH-statements : EUH210 - Safety data sheet available on request.

#### 2.3. Other hazards

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

# Liquimatic D46

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated heavy paraffinic substance with national workplace exposure limit(s) (BE, BG, CZ, DK, FI, GB, GR, HU, IE, LT, LV, NL, PL, PT, RO, SE, SK, IS, NO, CH)	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627-25, UK-01-1759217276-5	≥ 50 – < 70	Not classified
Distillates,hydrotreated heavy paraffinic substance with national workplace exposure limit(s) (BE, BG, CZ, DK, FI, GB, GR, HU, IE, LT, LV, NL, PL, PT, RO, SE, SK, IS, NO, CH)	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627-25, UK-01-1759217276-5	≥ 10 – < 30	Asp. Tox. 1, H304
2,6 Di-tert-butylphenol	CAS-No.: 128-39-2 EC-No.: 204-884-0 REACH-no: 01-2119490822-33, UK-01-2429337705-7	≥ 0.1 – < 1	Skin Irrit. 2, H315 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
distillates (petroleum), solvent-dewaxed light paraffinic; baseoil -unspecified substance with national workplace exposure limit(s) (BE, BG, CZ, DK, FI, GB, GR, HU, IE, LT, LV, NL, PL, PT, RO, SE, SK, IS, NO, CH)	CAS-No.: 64742-56-9 EC-No.: 265-159-2 EC Index-No.: 649-469-00-9 REACH-no: 01-2119480132-48	< 1	Asp. Tox. 1, H304
Distillates (petroleum), solvent-dewaxed heavy paraffinic substance with national workplace exposure limit(s) (BE, BG, CZ, DK, FI, GB, GR, HU, IE, LT, LV, NL, PL, PT, RO, SE, SK, IS, NO, CH)	CAS-No.: 64742-65-0 EC-No.: 265-169-7 REACH-no: 01-2119471299-27, UK-01-0119695008-1	< 1	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated light paraffinic substance with national workplace exposure limit(s) (BE, BG, CZ, DK, FI, GB, GR, HU, IE, LT, LV, NL, PL, PT, RO, SE, SK, IS, NO, CH)	CAS-No.: 64742-55-8 EC-No.: 265-158-7 REACH-no: 01-2119487077-29	< 1	Asp. Tox. 1, H304
Methyl Methacrylate substance with national workplace exposure limit(s) (GB, NO); substance with a Community workplace exposure limit	CAS-No.: 80-62-6 EC-No.: 201-297-1 EC Index-No.: 607-035-00-6 REACH-no: 01-2119452498-28	< 0.1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Chronic 3, H412
C16-18-(even numbered, saturated and unsaturated)-alkylamines	CAS-No.: 1213789-63-9 EC-No.: 627-034-4 REACH-no: 01-2119473797-19, UK-01-7336349961-4	< 0.1	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)

# Liquimatic D46

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Dipropylene glycol monomethyl ether substance with national workplace exposure limit(s) (GB, NO); substance with a Community workplace exposure limit	CAS-No.: 34590-94-8 EC-No.: 252-104-2 REACH-no: 01-2119450011- 60	< 0.1	Not classified
NAPHTHALENE substance with national workplace exposure limit(s) (NO); substance with a Community workplace exposure limit	CAS-No.: 91-20-3 EC-No.: 202-049-5 EC Index-No.: 601-052-00-2 REACH-no: 01-2119561346- 37	< 0.1	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Carc. 2, H351 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Specific concentration limits:		
Name	Product identifier	Specific concentration limits
2,6 Di-tert-butylphenol	CAS-No.: 128-39-2 EC-No.: 204-884-0 REACH-no: 01-2119490822- 33, UK-01-2429337705-7	( 35 ≤C < 100) Skin Irrit. 2, H315

Comments : A petroleum product. DMSO extract < 3 % weight (IP 346)  
Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: If you feel unwell, seek medical advice.
First-aid measures after inhalation	: Move the affected person away from the contaminated area and into the fresh air. If you feel unwell, seek medical advice.
First-aid measures after skin contact	: Take off contaminated clothing and wash it before reuse. Gently wash with plenty of soap and water.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Get medical advice/attention if you feel unwell. Do NOT induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: None under normal use. Inhalation may cause irritation (cough, short breathing, difficulty in breathing).
Symptoms/effects after skin contact	: Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: May cause slight irritation.
Symptoms/effects after ingestion	: Although not classified, the product contains mineral oil. If aspirated into the lungs e.g. through vomiting after ingestion, admit to hospital immediately.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Dry chemical, CO <sub>2</sub> , dry sand, or alcohol-resistant foam.
Unsuitable extinguishing media	: Do not use a heavy water stream.

# Liquimatic D46

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 5.2. Special hazards arising from the substance or mixture

- Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
- Hazardous decomposition products in case of fire : Toxic fumes may be released. Carbon monoxide. Carbon dioxide.

### 5.3. Advice for firefighters

- Precautionary measures fire : Keep container closed when not in use.
- Firefighting instructions : Prevent fire fighting water from entering the environment. Use water spray or fog for cooling exposed containers.
- Protection during firefighting : Self-contained breathing apparatus.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Clean up any spills as soon as possible, using an absorbent material to collect it.

#### 6.1.1. For non-emergency personnel

- Protective equipment : Wear recommended personal protective equipment.
- Emergency procedures : Evacuate unnecessary personnel. Caution : this product can cause the floor to be very slippery.

#### 6.1.2. For emergency responders

No additional information available

### 6.2. Environmental precautions

Do not allow to enter drains or water courses. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Clear up rapidly by scoop or vacuum. Collect leaking and spilled liquid in sealable containers as far as possible. Absorb remaining liquid with sand or inert absorbent and remove to safe place. Notify authorities if product enters sewers or public waters. This material and its container must be disposed of in a safe way, and as per local legislation.

### 6.4. Reference to other sections

No additional information available

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.
- Precautions for safe handling : Do not eat, drink or smoke when using this product.
- Hygiene measures : Wear personal protective equipment. Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Store in a well-ventilated place. Keep container tightly closed.
- Storage conditions : Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep container closed when not in use. Store in a dry place.
- Incompatible products : Oxidizing agent. Strong acids. Strong bases.
- Storage area : Store in a well-ventilated place.
- Special rules on packaging : Store in a closed container.

# Liquimatic D46

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

<b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
<b>United Kingdom - Occupational Exposure Limits</b>	
WEL TWA (OEL TWA) [1]	5 mg/m <sup>3</sup> 8H
Regulatory reference	EU OEL (Europe).
<b>Methyl Methacrylate (80-62-6)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Methyl methacrylate
IOEL TWA [ppm]	50 ppm
IOEL STEL [ppm]	100 ppm
Regulatory reference	COMMISSION DIRECTIVE 2009/161/EU
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Methyl methacrylate
WEL TWA (OEL TWA) [1]	208 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	50 ppm
WEL STEL (OEL STEL)	416 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	100 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>distillates (petroleum), solvent-dewaxed light paraffinic; baseoil -unspecified (64742-56-9)</b>	
<b>United Kingdom - Occupational Exposure Limits</b>	
WEL TWA (OEL TWA) [1]	5 mg/m <sup>3</sup> 8H
Regulatory reference	EU OEL (Europe).
<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)</b>	
<b>United Kingdom - Occupational Exposure Limits</b>	
WEL TWA (OEL TWA) [1]	5 mg/m <sup>3</sup> 8H
Regulatory reference	EU OEL (Europe).
<b>Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)</b>	
<b>United Kingdom - Occupational Exposure Limits</b>	
WEL TWA (OEL TWA) [1]	5 mg/m <sup>3</sup> 8H
Regulatory reference	EU OEL (Europe).
<b>NAPHTHALENE (91-20-3)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Naphthalene
IOEL TWA	50 mg/m <sup>3</sup>

# Liquimatic D46

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

NAPHTHALENE (91-20-3)	
IOEL TWA [ppm]	10 ppm
Remark	(Year of adoption 2010)
Regulatory reference	COMMISSION DIRECTIVE 91/322/EEC; SCOEL Recommendations
Dipropylene glycol monomethyl ether (34590-94-8)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	(2-Methoxymethylethoxy)-propanol
IOEL TWA	308 mg/m <sup>3</sup>
IOEL TWA [ppm]	50 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
United Kingdom - Occupational Exposure Limits	
Local name	(2-methoxymethylethoxy) propanol
WEL TWA (OEL TWA) [1]	308 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	50 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Distillates,hydrotreated heavy paraffinic (64742-54-7)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	5 mg/m <sup>3</sup> 8H
Regulatory reference	EU OEL (Europe).

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

No additional information available

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

### 8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



# Liquimatic D46

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 8.2.2.1. Eye and face protection

#### Eye protection:

Chemical goggles or face shield

### 8.2.2.2. Skin protection

#### Hand protection:

Gloves

### 8.2.2.3. Respiratory protection

#### Respiratory protection:

No respiratory protection needed under normal use conditions

### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

No additional information available

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Blue.
Appearance	: Liquid.
Odour	: mild.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: > 320 °C
Flammability	: Not flammable, Heating may cause a fire.
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 196 °C PMCC
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 46.9 mm²/s @40C
Solubility	: Material nearly insoluble in water. Soluble in organic solvents.
Partition coefficient n-octanol/water (Log Kow)	: ≈ 7 Not determined. Typical for mineral oil
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: 0.873
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

Additional information : The product is a complex mixture, the majority of which would not be classed as a VOC.  
However it cannot be discounted that trace or low levels of VOCs may be present.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

# Liquimatic D46

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 10.2. Chemical stability

Stable under normal conditions of use.

### 10.3. Possibility of hazardous reactions

No additional information available

### 10.4. Conditions to avoid

Extremely high or low temperatures. Moisture.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LD50 oral rat > 15000 mg/kg Source: IUCLID

LD50 dermal rabbit > 5000 mg/kg Source: IUCLID

#### Methyl Methacrylate (80-62-6)

LD50 oral rat 7900 mg/kg Source: NITE, HSDB, ChemIDplus

LD50 dermal rabbit > 5000 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

LC50 Inhalation - Rat [ppm] 7093 ppm Source: HSDB

#### 2,6 Di-tert-butylphenol (128-39-2)

LD50 oral rat > 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)

#### C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)

LD50 dermal rat > 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

#### distillates (petroleum), solvent-dewaxed light paraffinic; baseoil -unspecified (64742-56-9)

LD50 oral rat > 5000 mg/kg Source: ECHA

LD50 dermal rabbit > 2000 mg/kg Source: EHCA

LC50 Inhalation - Rat (Dust/Mist) > 2.18 mg/l Source: ECHA

#### Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

LD50 oral rat > 5000 mg/kg Source: IUCLID

LD50 dermal rabbit > 2000 mg/kg Source: IUCLID

#### NAPHTHALENE (91-20-3)

LD50 oral rat > 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)

# Liquimatic D46

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>NAPHTHALENE (91-20-3)</b>	
LD50 dermal rabbit	2500 mg/kg Source: ChemIDplus
<b>Dipropylene glycol monomethyl ether (34590-94-8)</b>	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 19020 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	9510 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met)
Additional information	: Repeated exposure may cause skin dryness or cracking.
<b>C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)</b>	
pH	11.7 Temp.: 20 °C
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met)
<b>C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)</b>	
pH	11.7 Temp.: 20 °C
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified
Additional information	: This product contains mineral oils which are considered to be severely refined and not considered to be carcinogenic under IARC. All of the oils in this product have been demonstrated to contain less than 3% extractables by the IP346 test
<b>Methyl Methacrylate (80-62-6)</b>	
IARC group	3 - Not classifiable
<b>NAPHTHALENE (91-20-3)</b>	
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
<b>NAPHTHALENE (91-20-3)</b>	
LOAEL (animal/female, F1)	450 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: other:
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)
<b>Methyl Methacrylate (80-62-6)</b>	
STOT-single exposure	May cause respiratory irritation.
<b>C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)</b>	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
<b>2,6 Di-tert-butylphenol (128-39-2)</b>	
NOAEL (oral, rat, 90 days)	100 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents), Guideline: EU Method B.7 (Repeated Dose (28 Days) Toxicity (Oral))
<b>C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)</b>	
NOAEL (oral, rat, 90 days)	3.25 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
STOT-repeated exposure	May cause damage to organs (gastro-intestinal tract, immune system, liver) through prolonged or repeated exposure (oral).

# Liquimatic D46

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

NAPHTHALENE (91-20-3)	
LOAEL (oral, rat, 90 days)	400 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
LOAEC (inhalation, rat, vapour, 90 days)	0.011 mg/l air Animal: rat, Guideline: EPA OPP 82-4 (90-Day Inhalation Toxicity), Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
NOAEL (oral, rat, 90 days)	200 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)

Dipropylene glycol monomethyl ether (34590-94-8)	
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: other:
Aspiration hazard	: Not classified
Additional information	: Although not classified, the product contains mineral oil. If aspirated into the lungs e.g. through vomiting after ingestion, admit to hospital immediately.

Liquimatic D46	
Viscosity, kinematic	46.9 mm²/s @40C
Methyl Methacrylate (80-62-6)	
Viscosity, kinematic	0.561 mm²/s
C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)	
Viscosity, kinematic	5.245 mm²/s

### 11.2. Information on other hazards

#### 11.2.1. Endocrine disrupting properties

No additional information available

#### 11.2.2. Other information

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met

## SECTION 12: Ecological information

### 12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified  
Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.  
Not rapidly degradable  
Additional information : Based on available data, the classification criteria are not met.

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LC50 - Fish [1]	> 5000 mg/l
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID
Methyl Methacrylate (80-62-6)	
LC50 - Fish [1]	368.1 mg/l Source: HSDB
EC50 - Crustacea [1]	69 mg/l Source: NITE
EC50 72h - Algae [1]	> 110 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

# Liquimatic D46

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Methyl Methacrylate (80-62-6)	
LOEC (chronic)	68 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	37 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	9.4 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) Duration: '35 d'
2,6 Di-tert-butylphenol (128-39-2)	
LC50 - Fish [1]	1.4 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	0.45 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	3.6 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	1.4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	3.9 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [2]	1.2 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	0.086 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.035 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)	
LC50 - Fish [1]	0.84 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
LC50 - Fish [2]	4.21 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	0.32 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	0.98 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	0.46 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	0.38 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
LOEC (chronic)	0.032 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.013 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
LC50 - Fish [1]	> 5000 mg/l Source: IUCLID
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID
NAPHTHALENE (91-20-3)	
LC50 - Fish [1]	1.6 mg/l
EC50 - Crustacea [1]	2.16 mg/l
NOEC (chronic)	0.59 mg/l Test organisms (species): Daphnia pulex Duration: '125 d'
Dipropylene glycol monomethyl ether (34590-94-8)	
LC50 - Fish [1]	> 1000 mg/l Test organisms (species): Poecilia reticulata
EC50 - Other aquatic organisms [1]	1930 mg/l Test organisms (species): other aquatic crustacea:
EC50 72h - Algae [1]	> 969 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

# Liquimatic D46

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Dipropylene glycol monomethyl ether (34590-94-8)

EC50 96h - Algae [1]	> 969 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	0.5 mg/l Test organisms (species): Daphnia magna Duration: '22 d'
NOEC (chronic)	≥ 0.5 mg/l Test organisms (species): Daphnia magna Duration: '22 d'

### 12.2. Persistence and degradability

#### Liquimatic D46

Persistence and degradability	Not established.
-------------------------------	------------------

#### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Persistence and degradability	Not established.
-------------------------------	------------------

### 12.3. Bioaccumulative potential

#### Liquimatic D46

Partition coefficient n-octanol/water (Log Kow)	≈ 7 Not determined. Typical for mineral oil
---	---

#### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
Partition coefficient n-octanol/water (Log Kow)	≈ 7 Not determined. Typical for mineral oil

#### Methyl Methacrylate (80-62-6)

Partition coefficient n-octanol/water (Log Pow)	1.38 Source: HSDB
---	-------------------

#### distillates (petroleum), solvent-dewaxed light paraffinic; baseoil -unspecified (64742-56-9)

Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
---	------------------------

#### Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
---	------------------------

#### NAPHTHALENE (91-20-3)

Partition coefficient n-octanol/water (Log Pow)	3.3 Source: hsbdb
---	-------------------

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product/Packaging disposal recommendations	: Dispose of contents/container to a hazardous or special waste collection point.
European List of Waste (LoW) code	: 13 02 05* - mineral-based non-chlorinated engine, gear and lubricating oils

# Liquimatic D46

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

HP Code : HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

### SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.2. UN proper shipping name</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.3. Transport hazard class(es)</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Not applicable

#### Transport by sea

Not applicable

#### Air transport

Not applicable

#### Inland waterway transport

Not applicable

#### Rail transport

Not applicable

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### 15.1.1. EU-Regulations

###### REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

###### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

###### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

# Liquimatic D46

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

### 15.1.2. National regulations

#### United Kingdom

British National Regulations : GB CLP.

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Abbreviations and acronyms:	
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DNEL	Derived-No Effect Level
EC-No.	European Community number
ED	Endocrine disrupting properties
IARC	International Agency for Research on Cancer
LC50	Median lethal concentration
LD50	Median lethal dose
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
SDS	Safety Data Sheet
STP	Sewage treatment plant
VOC	Volatile Organic Compounds
WGK	Water Hazard Class
vPvB	Very Persistent and Very Bioaccumulative

# Liquimatic D46

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Data sources	: ECHA (European Chemicals Agency). REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006. Supplier's safety documents.
Training advice	: Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H- and EUH-statements:	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
EUH210	Safety data sheet available on request.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.