

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

Product name Vivace XT

Product number 7754

Internal identification GHS21679

EU REACH registration notes Due to the transition process from EU to UK REACH, our SDS no longer show EU REACH

numbers on English SDS as they do not apply to the UK market. UK REACH numbers will be shown as they become available from our suppliers. This product is formulated in compliance

with both EU and UK REACH

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Metal Working Fluid

**Uses advised against**No specific uses advised against are identified.

# 1.3. Details of the supplier of the safety data sheet

**Supplier** Morris Lubricants

Castle Foregate Shrewsbury Shropshire SY1 2EL

+44 (0) 1743 232200 +44 (0) 1743 353584

sds@morris-lubricants.co.uk

# 1.4. Emergency telephone number

**Emergency telephone** +44(0)1743 232200 (08.45 - 17.00 GMT)

## SECTION 2: Hazards identification

## 2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)

Physical hazards Not Classified

**Health hazards** Asp. Tox. 1 - H304

Environmental hazards Not Classified

Classification (67/548/EEC or -

1999/45/EC)

# 2.2. Label elements

Hazard pictograms



## Vivace XT

Signal word Danger

**Hazard statements** H304 May be fatal if swallowed and enters airways.

Precautionary statements P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501a Dispose of container/contents to a hazardous or special waste collection point.

Contains Lubricating Oil (Petroleum) C15-30 hydrotreated neutral oil-based, Distillates (petroleum),

solvent-dewaxed heavy paraffinic

#### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

## 3.2. Mixtures

Lubricating Oil (Petroleum) C15-30 hydrotreated neutral oil-

30-60%

based

CAS number: 72623-86-0 EC number: 276-737-9

Classification Classification (67/548/EEC or 1999/45/EC)

Asp. Tox. 1 - H304

Distillates (petroleum), solvent-dewaxed heavy paraffinic

30-60%

CAS number: 64742-65-0 EC number: 265-169-7 UK REACH registration number: UK-01-

0119695008-1-XXXX

Classification Classification (67/548/EEC or 1999/45/EC)

Asp. Tox. 1 - H304 -

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Ingredient notes A petroleum product. DMSO extract < 3 % weight ( IP 346 )

# SECTION 4: First aid measures

# 4.1. Description of first aid measures

General information Get medical attention if any discomfort continues.

**Inhalation** If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and

keep warm and at rest in a position comfortable for breathing. Get medical attention

immediately.

Ingestion Get medical attention if any discomfort continues. Do not induce vomiting. Product contains

petroleum based material, which, if aspirated into the lungs may result in chemical

pneumonia.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms

occur after washing.

# 4.2. Most important symptoms and effects, both acute and delayed

General information If aspiration into the lungs is suspected, eg when vomiting, admit to hospital immediately.

## Vivace XT

**Inhalation** Upper respiratory irritation.

Ingestion May cause discomfort if swallowed. The product contains mineral oil, which if aspirated into

the lungs through vomiting after ingestion, may result in chemical pneumonia. May be fatal if

swallowed and enters airways.

**Skin contact** Prolonged contact may cause redness, irritation and dry skin.

**Eye contact** Irritation of eyes and mucous membranes.

#### 4.3. Indication of any immediate medical attention and special treatment needed

# SECTION 5: Firefighting measures

## 5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

Specific hazards Heat from fire could result in drums bursting

Hazardous combustion

products

Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m³. Oxides of carbon. Oxides of nitrogen. Fire may also create other unidentified organic

gases some of which may be toxic.

# 5.3. Advice for firefighters

Protective actions during

firefighting

Control run-off water by containing and keeping it out of sewers and watercourses.

Special protective equipment

for firefighters

Wear self-contained breathing apparatus.

# SECTION 6: Accidental release measures

# 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions For personal protection, see Section 8. In case of spills, beware of slippery floors and

surfaces.

#### 6.2. Environmental precautions

Environmental precautions Contain spillage with sand or earth. Avoid the spillage or runoff entering drains, sewers or

watercourses. The product is insoluble in water and will spread on the water surface.

# 6.3. Methods and material for containment and cleaning up

Methods for cleaning up Contain spillage with sand or earth. Collect spillage for reclamation or disposal in sealed

containers via a licensed waste contractor. Avoid water contacting spilled material or leaking containers. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. In case of

spillage on water prevent the spread by use of suitable barrier equipment

## 6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health

hazards. For waste disposal, see section 13.

#### SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

## Vivace XT

Usage precautions Avoid spilling. Always remove oil with soap and water or skin cleaning agent, never use

organic solvents. Do not use oil-contaminated clothing or shoes, and do not put rags

moistened with oil into pockets.

Advice on general occupational hygiene

Do not eat, drink or smoke when using this product.

# 7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

**Storage class** Miscellaneous hazardous material storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

# SECTION 8: Exposure controls/Personal protection

## 8.1. Control parameters

## Occupational exposure limits

# Lubricating Oil (Petroleum) C15-30 hydrotreated neutral oil-based

Long-term exposure limit (8-hour TWA): ACGIH 5 mg/m³

## Distillates (petroleum), solvent-dewaxed heavy paraffinic

Long-term exposure limit (8-hour TWA): ACGIH 5 mg/m<sup>3</sup> Short-term exposure limit (15-minute): ACGIH 10 mg/m<sup>3</sup>

ACGIH = American Conference of Governmental Industrial Hygienists.

# Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS: 64742-65-0)

**DNEL** - Inhalation; : 5.4 mg/m<sup>3</sup>

**PNEC** - ; 9.33 mg/kg

Chlorinated Paraffin C18-C30 (CAS: 63449-39-8)

**DNEL** Industry - Inhalation; Long term systemic effects: 2.35 mg/m³

Industry - Dermal; Long term systemic effects: 20 mg/kg bw/day Consumer - Oral; Long term systemic effects: 0.167 mg/kg bw/day

Consumer - Dermal; systemic effects: 8.3 mg/kg bw/day

PNEC Fresh water; 5.5 μg/l

marine water; 1.1 µg/l

STP; 60 mg/l

Sediment (Freshwater); 33.1 mg/kg

Soil; 26.9 g/kg

N-methyl-N-[C18-(unsaturated)alkanoyl]glycine (CAS: 110-25-8)

## Vivace XT

**DNEL** Workers - Inhalation; Long term systemic effects: 0.2 mg/m³

Workers - Inhalation; Short term systemic effects: 18 mg/m³ Workers - Inhalation; Long term local effects: 0.01 mg/m³ Workers - Inhalation; Short term local effects: 18 mg/m³ Workers - Dermal; Long term systemic effects: 10 mg/kg/day Workers - Dermal; Short term systemic effects: 100 mg/kg/day

Workers - Dermal; Long term, Short term local effects:

General population - Inhalation; Long term systemic effects: 0.1 mg/m³ General population - Inhalation; Short term systemic effects: 9 mg/m³ General population - Inhalation; Long term local effects: 0.005 mg/m³ General population - Inhalation; Short term local effects: 9 mg/m³ General population - Dermal; Long term systemic effects: 5 mg/kg/day General population - Dermal; Short term systemic effects: 50 mg/kg/day General population - Dermal; Long term, Short term local effects: General population - Oral; Long term systemic effects: 5 mg/kg/day General population - Oral; Short term systemic effects: 92 mg/kg/day

PNEC - Fresh water; 0.00043 mg/l

marine water; 0.000043 mg/lSediment (Freshwater);Sediment (Marinewater);

- Soil;

- STP; 13 mg/l

## 8.2. Exposure controls

#### Protective equipment





Appropriate engineering

controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or

face shield.

Hand protection The most suitable glove should be chosen in consultation with the glove

supplier/manufacturer, who can provide information about the breakthrough time of the glove

material.

Other skin and body

protection

Use barrier creams to prevent skin contact.

promptly with soap and water if skin becomes contaminated.

**Respiratory protection**No specific recommendations. Respiratory protection must be used if the airborne

contamination exceeds the recommended occupational exposure limit.

Thermal hazards Not anticipated under normal conditions of use. The product is combustible if heated

excessively and an ignition source is applied.

**Environmental exposure** 

controls

Do not allow product to contaminate land.

#### SECTION 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

## Vivace XT

**Appearance** Amber liquid

Odour Characteristic. Oil-like.

Odour threshold Not determined.

Ηq Not applicable.

Melting point Not applicable.

Initial boiling point and range >320°C @ 101.3 kPa

165°C Pensky-Martens closed cup. Flash point

Upper/lower flammability or

explosive limits

Not known.

Other flammability Product is not flammable but on excessive heating may become combustible.

Vapour density Not determined.

Relative density 0.870 @ 15.6°C

Insoluble in water. Soluble in the following materials: Organic solvents. Solubility(ies)

Partition coefficient Not determined. Not determined. **Auto-ignition temperature Decomposition Temperature** Not determined.

13.3 cSt @ 40°C Viscosity

**Explosive properties** Not considered to be explosive. Explosive under the influence

of a flame

Not considered to be explosive.

The mixture itself has not been tested but none of the ingredient substances meet the criteria Oxidising properties

for classification as oxidising.

9.2. Other information

Volatile organic compound The product is a complex mixture, the majority of which would not be classed as a VOC.

However it cannot be discounted that trace or low levels of VOCs may be present.

# SECTION 10: Stability and reactivity

# 10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stable at normal ambient temperatures and when used as recommended. Stability

# 10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Unlikely to occur under normal conditions of use.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

# 10.6. Hazardous decomposition products

# Vivace XT

Hazardous decomposition

Oxides of carbon. Protection against nuisance dust must be used when the airborne

products

concentration exceeds 10 mg/m<sup>3</sup>.

# SECTION 11: Toxicological information

## 11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅o) Not expected to be highly toxic based on information of ingredients.

Acute toxicity - dermal

Notes (dermal LD<sub>50</sub>) Not expected to be highly toxic based on information of ingredients.

Acute toxicity - inhalation

Notes (inhalation LC<sub>50</sub>) The product is unlikely to present any significant inhalation hazard at ambient temperatures

and under normal conditions of use.

Serious eye damage/irritation

Serious eye damage/irritation May cause mild, short lasting discomfort to eyes.

Respiratory sensitisation

**Respiratory sensitisation** No evidence to suggest the product will be a respiratory sensitiser.

Skin sensitisation

**Skin sensitisation** Not expected to be a skin sensitizer based on information on components.

Reproductive toxicity

Reproductive toxicity - fertility No data available to suggest the product will cause reproductive toxicity.

Aspiration hazard

Aspiration hazard Kinematic viscosity <= 20.5 cSt @ 40 C

General information This product has low toxicity. Only large quantities are likely to have adverse effects on

human health.

**Inhalation** High concentrations of vapours may irritate respiratory system and lead to headache, fatigue,

nausea and vomiting.

**Ingestion** Swallowing significant quantities may cause discomfort, nausea, diarrhoea and irritation of the

digestive tract. Aspiration into the lungs (e.g. through vomiting) after ingestion can be hazardous with possible resultant chemically induced pneumonia. May be fatal if swallowed

and enters airways.

Skin contact Skin irritation should not occur when used as recommended. Repeated exposure may cause

skin dryness or cracking.

**Eye contact** May cause temporary eye irritation.

Acute and chronic health Prolonged or repeated contact with used oil may cause serious skin diseases, such as

hazards dermatitis and skin cancer.

SECTION 12: Ecological information

# 12.1. Toxicity

# 12.2. Persistence and degradability

Persistence and degradability The product is not classed as being readily biodegradable by OECD test methods but is

considered inherently biodegradable.

Biological oxygen demand Not determined.

## Vivace XT

Chemical oxygen demand Not determined.

## 12.3. Bioaccumulative potential

Bioaccumulative potential Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.

Partition coefficient Not determined.

12.4. Mobility in soil

**Mobility**The product is non-volatile. The product is insoluble in water and will spread on the water

surface.

Henry's law constant Not determined.

## 12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

# **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site

in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

Waste class European Waste Catalogue (EWC) Code = 13 02 04\* (mineral based chlorinated engine, gear

& lubricating oils)

# **SECTION 14: Transport information**

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

## 14.1. UN number

Not applicable.

## 14.2. UN proper shipping name

Not applicable.

# 14.3. Transport hazard class(es)

No transport warning sign required.

# 14.4. Packing group

Not applicable.

## 14.5. Environmental hazards

# Environmentally hazardous substance/marine pollutant

No.

# 14.6. Special precautions for user

Not applicable.

## 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

## Vivace XT

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

## SECTION 15: Regulatory information

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Health and Safety at Work etc. Act 1974 (as amended).

The Pollution Prevention and Control Act 1999.

Special Waste regulations 1996.

Control of Pollution (Oil Storage) (England) Regulations 2001

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009

No. 716).

Guidance Workplace Exposure Limits EH40.

Safety Data Sheets for Substances and Preparations.

# 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

## Inventories

## **EU - EINECS/ELINCS**

All the ingredients are listed or exempt.

#### Canada - DSL/NDSL

All the ingredients are listed or exempt.

# US - TSCA

All the ingredients are listed or exempt.

# Korea - KECI

All the ingredients are listed or exempt.

# China - IECSC

All the ingredients are listed or exempt.

# Philippines - PICCS

All the ingredients are listed or exempt.

# New Zealand - NZIOC

All the ingredients are listed or exempt.

# SECTION 16: Other information

**Revision comments** NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date 18/05/2022

Revision 4

Supersedes date 26/07/2021

SDS number 21679

Risk phrases in full Not classified.

Hazard statements in full H304 May be fatal if swallowed and enters airways.

# Vivace XT

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.