



Product Information:

SERVOL 15W-40

MULTIGRADE ENGINE OIL – SUPERIOR QUALITY

(Formerly known as – Servol Performance Plus 15W-40)

Description

Servol 15W-40 is manufactured from high quality mineral oils and a high performance additive system. This grade is designed for use in petrol and diesel engines and their turbocharged versions. Servol Performance Plus 15W-40 provides a good level of engine cleanliness and controls the formation of high temperature lacquers and low temperature sludges. Anti-wear technology ensures maximum component life, together with protection from oxidation, rust and corrosion.

Applications

Typical applications for Servol 15W-40 include pre-2004 passenger cars and vans and commercial vehicles (Euro 1 and Euro 2 compliant), where the following would have been originally stated: MB 228.1, MAN 271, Mack EO-L, Volvo VDS and VW 505.00.

Note: This product must never be used in engines incorporating after-treatment devices. This includes: exhaust gas re-circulation (EGR), diesel particulate filters (DPFs) and adblue systems.

Performance Levels

API CG-4 / CF-4 / SJ / SL

Physical Characteristics

Density at 15.6 °C	0.880
Viscosity @ 100 °C, cSt.	14.4
Viscosity @ 40 °C, cSt.	102.0
Viscosity Index	143
Flash Point (Closed) °C	201
TBN, mg/KOH/g	9.7
Pour Point, °C	-36

Figures based on average production values.

Part No.s: SPP001, SPP005, SPP025, SPP205

(TDS Servol 15W-40 - 120716 Issue 1)

