



Product Information:

MULTITRANS VTS

VERSATILE TRANSMISSION FLUID

Description

Multitrans VTS is a highly versatile transmission fluid that allows for rationalisation whilst providing high levels of component protection and system efficiency. The product has been developed to reduce stock inventories, where operators have a wide and varied fleet profile, whilst ensuring maximum service life and component longevity.

Features

- Extended drain interval capability
- Provides high levels of component protection
- Outstanding low temperature fluidity
- Superior oxidation and thermal stability control
- Advanced wear control
- Improved friction retention

Applications

Multitrans VTS is recommended for use in the automatic transmissions of commercial vehicles, buses, coaches, off-highway / construction equipment and passenger cars. The product may also be used in certain hydraulic applications, where a fluid of this type and specification is required.

Performance Levels

General Motors DEXRON® IIIH*

Ford MERCON® / MERCON V®*

MAN 339 Type Z-1, Z-2, V-1, V-2

MB 236.1, 236.5, 236.6, 236.7, 236.9, 236.10

Voith H.55.6335.xx

ZF TE-ML 02F, 03D, 04D, 09, 11A, 11B, 14A, 14B, 16L, 17C

Allison C-4 / TES-389

Volvo 97340 / 97341

Caterpillar TO-2

*Ford and GM vehicles -model year prior to 2006.

Physical Characteristics

Appearance	Red
Density at 15.6 °C	0.850
Viscosity at 100 °C, cSt.	7.22
Viscosity at 40 °C, cSt.	31.5
Viscosity Index	208
Flash Point (Closed) °C	179
Pour Point, °C	-42

Figures based on average production values.

Part No.s: VTS025, VTS205

(TDS Multitrans VTS 050123 – Issue 4)

