



Product Information:

SERVOL 5W-30

MID-SAPS PASSENGER CAR ENGINE OIL

Description

Servol 5W-30 is a mid-SAPS technology engine oil formulated to meet the demands and fuel efficiency expectations of petrol and diesel engines, where a low viscosity oil of this type is required. Servol 5W-30 has been developed for use in engines using exhaust after treatment devices, including diesel particulate filters (DPFs) and Adblue systems. Servol 5W-30 flows readily on cold starts protecting all critical engine components whilst the engine reaches normal operating temperatures.

Servol 5W-30 is suitable for vehicles using hybrid electric technology.

Applications

Recommended for petrol and diesel engines, fitted in cars and vans, including turbo and supercharged versions requiring a low viscosity 5W-30 oil, specifying one of the performance levels listed below.

Performance Levels

ACEA C3
MB229.31
API SP

Physical Characteristics

Viscosity @ 100°C, cSt.	11.9
Viscosity @ 40°C, cSt.	73.5
Viscosity Index	161
Density @ 15.6°C	0.856
TBN, mg/KOH/g	7.0
Flash Point (Closed) °C	234
Pour Point °C	-42

Figures based on average production values.

Part No.s: SFT005, SFT025, SFT205

(TDS Servol 5W-30 – 220721 Issue 2)

