



Product Information: **MORRGREASE**

Description:

Premium performance multi-application grease with very high load carrying ability, excellent resistance to water, oxidation and corrosion, and outstanding performance in a wide range of temperatures.

Features:

- Suitable for a wide range of industrial machinery.
- Exceptional pressure and anti-wear performance.
- Provides high levels of corrosion protection.

Applications:

- Plain/rolling-element bearings
- Marine equipment
- Heavy mobile equipment
- Paper machinery
- Hot calendar stacks/hot roll tables
- Rolling mills
- Ingot buggies/slab mills
- Conveyors
- Gears

As with all greases used for the first time, check compatibility with the grease applied previously and if necessary purge bearings prior to application. Likewise, as a general rule, take care not to over-lubricate and apply the quantity of grease recommended by the bearing manufacturer.

Typical Properties:

NLGI Grade	2	
Texture	Buttery	
Appearance	Smooth	
Colour	Brown	
Operating Temperature Range	-25° to 160°C	
Penetration, Worked 60 Strokes	D217A	265-295
Timken OK Load, Kg/lb	D2509	27/60
Dropping Point, min.	D2265	>280
Four Ball Weld Load, Kg	D2596	400
Viscosity, 40°C	D7152	73 cSt
Viscosity 100°C	D7152	9.3 cSt

(TDS Morrgrease – 180822 Issue 1)

