Product Information:

MULTIVIS ECO VA 0W-30

SYNTHETIC TECHNOLOGY – MID-SAPS

Description

Multivis ECO VA 0W-30 is a synthetic technology advanced lubricant, designed for use in the latest engines, including those fitted with exhaust gas after-treatment devices.

Multivis ECO VA 0W-30 has the following benefits:

1. Increased engine efficiency.
2. Outstanding fuel economy.
3. Provides extended oil drain capability.
4. Rapid cold start flow that reduces noise and wear.
5. Increased film strength at high temperatures under all driving conditions.
6. High temperature deposit and anti-sludge control.
7. Low levels of volatility.

Applications

Multivis ECO VA 0W-30 is recommended for the latest petrol and diesel engines, including turbo-charged versions and those fitted with exhaust gas after-treatment devices such as particulate filters, catalytic converters, exhaust gas re-circulation, etc. Multivis ECO VA 0W-30 can be used where any of the following manufacturer's specifications are listed.

Performance Levels

ACEA C3
MB 229.52
BMW Longlife-04
BMW Longlife-19FE
Porsche C30

Approvals

Approved under VW Standard 504 00 and VW Standard 507 00

Physical Characteristics

Viscosity @ 100°C, cSt.	11.81
Viscosity @ 40 °C, cSt.	67.99
Viscosity Index	171
Density @ 15.6°C	0.850
Flash Point (Closed) °C	202
TBN, mg/KOH/g	8.0
Pour Point, °C	-42

Figures based on average production values.