

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Reference number: 22291 Issue date: 05/06/2023 Revision date: 05/06/2023 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form Product name Product code Type of product Vaporizer Product group Mixture
MD4 Aerosol
7733-036
Penetrating Fluid

: Aerosol

: Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

No additional information available

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

Morris Lubricants Castle Foregate SY1 2EL Shrewsbury – Shropshire United Kingdom T +44 (0) 1743 232200 sds@morris-lubricants.co.uk

1.4. Emergency telephone number

Emergency number

: +44 (0) 1743 232200 08.45 - 17.00 GMT

SECTION 2: Hazards identification

2.1 Classification of the substance or mixtur

2.1. Oldssmodifier of the Substance of mixture	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	
Aerosol, Category 1	H222;H229
Specific target organ toxicity – Repeated exposure, Category 1	H372
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412
Full text of H- and EUH-statements: see section 16	

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. Causes damage to organs (respiratory system) through prolonged or repeated exposure (if inhaled). Harmful to aquatic life with long lasting effects.

2.2. Label elements

z.z. Laber elements		
Labelling according to Regulation (EC) No. 1272/2008 [CLP]		
Hazard pictograms (CLP)		
	GHS02	GHS08
Signal word (CLP)	: Danger	
Contains	: HYDROCARBC 25%)	DNS C10 - C13 N-ALKANES, ISOALKANES, CYCLICS AROMATICS (2 -

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazard statements (CLP)	 H222 - Extremely flammable aerosol. H229 - Pressurised container: May burst if heated. H372 - Causes damage to organs (central nervous system) through prolonged or repeated exposure (if inhaled). H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP)	 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P260 - Do not breathe spray, vapours. P302+P352 - IF ON SKIN: Wash with plenty of soap and water. P273 - Avoid release to the environment. P280 - Wear protective gloves, protective clothing, eye protection, face protection.
2.3. Other hazards	

Other hazards which do not result in classification :

: Contains gas under pressure; may explode if heated.

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS (contains <0.1% 1,3-butadiene) substance with national workplace exposure limit(s) (GB)	CAS-No.: 68476-85-7 EC-No.: 270-704-2 EC Index-No.: 649-202-00-6 REACH-no: 01-2119485911- 31	≥ 30 – < 50	Flam. Gas 1, H220 Press. Gas (Liq.), H280
HYDROCARBONS C10 - C13 N-ALKANES, ISOALKANES, CYCLICS AROMATICS (2 -25%) substance with a Community workplace exposure limit	EC-No.: 919-164-8 REACH-no: 01-2119473977- 17	≥ 30 – < 50	STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 3, H412 EUH066
Hydrotreated Heavy Naphthenic Distillate substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 64742-52-5 EC-No.: 265-155-0 EC Index-No.: 649-465-00-7 REACH-no: 01-2119467170- 45	≥ 10 – < 30	Not classified
sulphonic acids, petroleum, sodium salts	CAS-No.: 68608-26-4 EC-No.: 271-781-5 REACH-no: 01-2119527859- 22	≥1-<5	Eye Irrit. 2, H319
ISOPENTYL ACETATE substance with national workplace exposure limit(s) (NO); substance with a Community workplace exposure limit	CAS-No.: 123-92-2 EC-No.: 204-662-3 EC Index-No.: 607-130-00-2	≥ 0.1 – < 1	Flam. Liq. 3, H226 Aquatic Chronic 3, H412 EUH066

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier		Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated light paraffinic substance with national workplace exposure limit(s) (BE, BG, CZ, DK, FI, GB, GR, HU, IE, LT, LV, NL, PL, PT, RO, SE, SK, IS, NO, CH)	CAS-No.: 64742-55-8 EC-No.: 265-158-7 EC Index-No.: 649-468-00-3 REACH-no: 01-2119487077- 29	< 0.1	Asp. Tox. 1, H304

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case. Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures	
First-aid measures general	: Get medical advice/attention if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. May have a narcotic effect at high concentrations.
First-aid measures after skin contact	: Wash skin with plenty of water. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do NOT induce vomiting. Rinse mouth out with water. Drink plenty of water. Get medical advice/attention.
4.2. Most important symptoms and effe	ects, both acute and delayed
Symptoms/effects after inhalation Symptoms/effects after skin contact Symptoms/effects after eye contact	 May cause headache, nausea and irritation of respiratory tract. Contact during a long period may cause light irritation. May cause eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media Unsuitable extinguishing media	Dry powder. Foam. Carbon dioxide.Do not use a heavy water stream.
5.2. Special hazards arising from the subst	tance or mixture
Fire hazard Explosion hazard Hazardous decomposition products in case of fire	 Extremely flammable aerosol. Pressurised container: May burst if heated. Toxic fumes may be released.
5.3. Advice for firefighters	
Firefighting instructions Protection during firefighting	 Use water spray or fog for cooling exposed containers. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measure	es
6.1. Personal precautions, protective equipr	ment and emergency procedures
6.1.1. For non-emergency personnel	
Protective equipment	: Wear recommended personal protective equipment.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Emergency procedures :	Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe spray, vapours.
6.1.2. For emergency responders	
Protective equipment :	Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
6.2. Environmental precautions	

Avoid release to the environment. Do not allow to enter drains or water courses. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up		
For containment	: Cover spill with non combustible material, e.g.: sand, earth, vermiculite. Collect spillage. Place in an appropriate container and dispose of the contaminated material at a licensed site.	
Methods for cleaning up	: Clear up rapidly by scoop or vacuum. Collect leaking and spilled liquid in sealable containers as far as possible.	
Other information	: Dispose of materials or solid residues at an authorized site.	
6.4. Reference to other sections		

For further information refer to section 13. Exposure controls and personal protection. See Section 8.

SECTION 7: Handling and storage			
7.1. Precautions for safe handling			
Precautions for safe handling Handling temperature Hygiene measures	 Avoid contact with skin and eyes. Do not breathe vapours, spray. ≤ 50 °C Do not eat, drink or smoke when using this product. Always wash hands after handling the product. 		
7.2. Conditions for safe storage, including any incompatibilities			
Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place. Keep cool.		

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS (contains <0.1% 1,3-butadiene) (68476-85-7)
United Kingdom - Occupational Exposure Limits

Local name	Liquefied petroleum gas	
WEL TWA (OEL TWA) [1]	1750 mg/m³	
WEL TWA (OEL TWA) [2]	1000 ppm	
WEL STEL (OEL STEL)	2180 mg/m ³	
WEL STEL (OEL STEL) [ppm]	1250 ppm	
Remark	Carc (Capable of causing cancer and/or heritable genetic damage (only applies if LPG contains more than 0.1% of buta-1,3-diene))	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hydrotreated Heavy Naphthenic Distillate (64742-52-5)			
EU - Indicative Occupational Exposure Limit (IOEL)			
IOEL TWA	5 mg/m³		
IOEL STEL	10 mg/m ³		
United Kingdom - Occupational Exposure Limits			
WEL TWA (OEL TWA) [1]	5 mg/m³		
WEL STEL (OEL STEL)	10 mg/m³		
Distillates (petroleum), hydrotreated light para	Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)		
United Kingdom - Occupational Exposure Limits			
WEL TWA (OEL TWA) [1]	5 mg/m³ 8H		
Regulatory reference	EU OEL (Europe).		
HYDROCARBONS C10 - C13 N-ALKANES, ISC	HYDROCARBONS C10 - C13 N-ALKANES, ISOALKANES, CYCLICS AROMATICS (2 -25%)		
EU - Indicative Occupational Exposure Limit (IOEL)			
IOEL TWA	350 mg/m³		
IOEL TWA [ppm]	56 ppm		
ISOPENTYL ACETATE (123-92-2)			
EU - Indicative Occupational Exposure Limit (IOEL)			
Local name	Isopentylacetate		
IOEL TWA	270 mg/m³		
IOEL TWA [ppm]	50 ppm		
IOEL STEL	540 mg/m³		
IOEL STEL [ppm]	100 ppm		
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC		

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses

e protection			
Туре	Field of application	Characteristics	Standard
Safety goggles	Dust	With side shields	EN 166

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Skin and body protection	
Туре	Standard
	EN 13034

Hand protection:

Chemical resistant gloves (according to European standard NF ISO 374-1 or equivalent)

Hand protection					
Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Nitrile rubber (NBR), Butyl rubber	6 (> 480 minutes)	0.5mm		EN 374-2, EN 374-3

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Respiratory protection			
Device	Filter type	Condition	Standard
Disposable half mask	Type A - High-boiling (>65 °C) organic compounds	Long term exposure	EN 140

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties		
9.1. Information on basic physical and chemical properties		
Physical state	: Liquid	
Colour	: brown.	
Appearance	: Aerosol.	
Odour	: Not available	
Odour threshold	: Not available	
Melting point	: Not applicable	
Freezing point	: Not available	
Boiling point	: Not available	
Flammability	: Extremely flammable aerosol.	
Explosive properties	: Pressurised container: May burst if heated.	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Explosive limits	: Not available
Lower explosion limit	: 0.5 vol %
Upper explosion limit	: 9 vol %
Flash point	: <0 °C
Auto-ignition temperature	: > 230 °C
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic @ 40°C	: Not available
Solubility	: Material insoluble in water. Soluble in organic solvents.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

% of flammable ingredients

: 77.38 %

9.2.2. Other safety characteristics No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information		
11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008		
Acute toxicity (oral)	: Not classified	
Acute toxicity (dermal)	: Not classified	
Acute toxicity (inhalation)	: Not classified	
Hydrotreated Heavy Naphthenic Distillate (64742-52-5)		

Hydrotreated Heavy Naphthenic Distillate (64/42-52-5)	
LD50 oral rat	> 5000 mg/kg Source: IUCLID
LD50 dermal rabbit	> 5000 mg/kg

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

sulphonic acids, petroleum, sodium salts (68608-26-4)		
LD50 dermal rabbit	> 5000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Remarks on results: other:	
LC50 Inhalation - Rat	> 1.9 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Remarks on results: other:	
HYDROCARBONS C10 - C13 N-ALKANES, ISC	DALKANES, CYCLICS AROMATICS (2 -25%)	
LD50 oral rat	> 15000 mg/kg	
LD50 dermal rat	> 3400 mg/kg	
LC50 Inhalation - Rat	> 13.1 mg/l	
ISOPENTYL ACETATE (123-92-2)		
LD50 dermal rabbit	> 5000 mg/kg Source: ChemIDPLUS	
Skin corrosion/irritation :	Not classified	
Serious eye damage/irritation :	Not classified	
Respiratory or skin sensitisation :	Not classified	
Germ cell mutagenicity :	Not classified	
Carcinogenicity :	Not classified	
Reproductive toxicity :	Not classified	
STOT-single exposure :	Not classified	
STOT-repeated exposure :	Causes damage to organs (central nervous system) through prolonged or repeated exposure (if inhaled).	
Hydrotreated Heavy Naphthenic Distillate (64	742-52-5)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
NOAEL (dermal, rat/rabbit, 90 days)	≈ 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)	
sulphonic acids, petroleum, sodium salts (68	608-26-4)	
NOAEL (oral, rat, 90 days)	500 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28- Day Oral Toxicity Study in Rodents)	
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)	
HYDROCARBONS C10 - C13 N-ALKANES, ISC	DALKANES, CYCLICS AROMATICS (2 -25%)	
STOT-repeated exposure	Causes damage to organs (central nervous system) through prolonged or repeated exposure (if inhaled).	
ISOPENTYL ACETATE (123-92-2)		
NOAEL (subchronic, oral, animal/female, 90 days)	443.07 mg/kg bodyweight Animal: , Animal sex: female	
Aspiration hazard :	Not classified	
MD4 Aerosol		
Vaporizer	Aerosol	
Hydrotreated Heavy Naphthenic Distillate (64	742-52-5)	
Viscosity, kinematic @ 40°C	22 mm²/s @40C	
HYDROCARBONS C10 - C13 N-ALKANES, ISC	DALKANES, CYCLICS AROMATICS (2 -25%)	
Viscosity, kinematic @ 40°C	1.2 mm²/s 40C	
ISOPENTYL ACETATE (123-92-2)		
Viscosity, kinematic @ 40°C	0.995 mm²/s	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information		
12.1. Toxicity		
Hazardous to the aquatic environment, short-term : (acute)	Harmful to aquatic life with long lasting effects. Not classified Harmful to aquatic life with long lasting effects.	
Hydrotreated Heavy Naphthenic Distillate (64	742-52-5)	
LC50 - Fish [1]	> 5000 mg/l Source: IUCLID	
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID	
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID	
sulphonic acids, petroleum, sodium salts (68	608-26-4)	
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
EC50 96h - Algae [1]	> 1000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
HYDROCARBONS C10 - C13 N-ALKANES, ISC	DALKANES, CYCLICS AROMATICS (2 -25%)	
LC50 - Fish [1]	10 – 100 mg/l Oncorhynchus mykiss	
EC50 - Crustacea [1]	10 – 22 mg/l Daphnia magna	
EC50 72h - Algae [1]	10 – 100 mg/l Pseudokirchneriella subcapitata	
NOEC chronic crustacea	0.28 mg/l Daphnia magna	
NOEC chronic algae	3 mg/l Pseudokirchneriella subcapitata	
ISOPENTYL ACETATE (123-92-2)		
LC50 - Fish [1]	36 mg/l Source: ECHA	
EC50 - Crustacea [1]	42 mg/l Source: ECHA	
12.2. Persistence and degradability		
HYDROCARBONS C10 - C13 N-ALKANES, ISC	DALKANES, CYCLICS AROMATICS (2 -25%)	
Biodegradation	74.7 % 28D	
12.3. Bioaccumulative potential		
Hydrotreated Heavy Naphthenic Distillate (64742-52-5)		
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID	
HYDROCARBONS C10 - C13 N-ALKANES, ISC	DALKANES, CYCLICS AROMATICS (2 -25%)	
Partition coefficient n-octanol/water (Log Pow)	> 4	
ISOPENTYL ACETATE (123-92-2)		
Partition coefficient n-octanol/water (Log Pow)	2.13 Source: ICSC	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.4. Mobility in soil
No additional information available
12.5. Results of PBT and vPvB assessment
No additional information available
12.6. Endocrine disrupting properties
No additional information available
12.7. Other adverse effects
No additional information available

SECTION 13: Disposal considerations	
13.1. Waste treatment methods	
Waste treatment methods Product/Packaging disposal recommendations European List of Waste (LoW) code HP Code	 Dispose of contents/container in accordance with licensed collector's sorting instructions. Do not pierce or burn, even after use. 15 01 10* - packaging containing residues of or contaminated by dangerous substances HP3 - "Flammable:" flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C; flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air; flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction; flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa; water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities; other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste. HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration. HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID				
ADR	IMDG	ΙΑΤΑ	ADN	RID
14.1. UN number or ID n	14.1. UN number or ID number			
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document description				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1 (0°C c.c.)	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1	2.1

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

IMDG	ΙΑΤΑ	ADN	RID
¥	· ·	· · · ·	
Not applicable	Not applicable	Not applicable	Not applicable
ards			
Dangerous for the	Dangerous for the	Dangerous for the	Dangerous for the
environment: No	environment: No	environment: No	environment: No
Marine pollutant: No			
n available			
s for user			
: 5F			
	0, 327, 344, 625		
	-9		
	4		
: D			
,			
: SG	90Y		
A)			
	•		
	-		
,			
	-		
: A1	40, A107, A0UZ		
	Not applicableIndext and sDangerous for the environment: No Marine pollutant: NoDangerous for the environment: No Marine pollutant: NoIn availablefor userfor userfor userSolutionPRImage: Solution (ADR)Image: ADR (Image: Solution (ADR))Image: ADR (Image: Solution (ADR))Image: ADR (Image: Solution (ADR))Image: ADR (Image: ADR (Imag	Not applicableNot applicableNot applicableNot applicableardsDangerous for the environment: No Marine pollutant: NoDangerous for the environment: NoavailableDangerous for the environment: NoDangerous for the environment: NoavailableDangerous for the environment: NoDangerous for the environment: Nothe availableDangerous for the environment: NoDangerous for the environment: Nothe availableEDangerous for the environment: NoDRESP07, LP200DRESP277 EDGESP277 EDGESP277 SDGESW1, SW22 SSG69SW1, SW22 SA)EA)EA)EA)EA)EDA)EDA)EDA)EDA)EDA)EDA) <t< td=""><td>Image: state of the service of the</td></t<>	Image: state of the service of the

Inland waterway transportClassification code (ADN): 5FSpecial provisions (ADN): 190, 327, 344, 625Limited quantities (ADN): 1 LExcepted quantities (ADN): E0

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Equipment required (ADN) Ventilation (ADN)	: PP, EX, A : VE01, VE04
Number of blue cones/lights (ADN)	: 1
Rail transport	
Classification code (RID)	: 5F
Special provisions (RID)	: 190, 327, 344, 625
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P207, LP200
Special packing provisions (RID)	: PP87, RR6, L2
Mixed packing provisions (RID)	: MP9
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W14
Special provisions for carriage - Loading, unloading	: CW9, CW12
and handling (RID)	
Colis express (express parcels) (RID)	: CE2
Hazard identification number (RID)	: 23

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

United Kingdom

British National Regulations	: The Control of Substances Hazardous to Health Regulations 2002 (S.I 2001 No.2677) with
	amendments.
	GB MCL (Mandatory Classification and Labelling).
	S.I. 2020 No 1577: The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 16: Other i	information
Abbreviations and acr	onyms:
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
ΙΑΤΑ	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
РВТ	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUF	I-statements:
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EU	IH-statements:
Asp. Tox. 1	Aspiration hazard, Category 1
EUH066	Repeated exposure may cause skin dryness or cracking.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 3	Flammable liquids, Category 3
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1

The classification complies with

: ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.