



## Product Information:

# MULTIVIS ECO V 0W-30

## SYNTHETIC TECHNOLOGY - FUEL EFFICIENT

### Description

Multivis ECO V 0W-30 is an engine oil providing not only the potential for fuel savings but a high level of component protection under a wide range of operating conditions in passenger cars or light commercial vehicles.

Synthetic technology base fluids provide rapid circulation and protection during cold starts, but also a strong low viscosity oil film that contributes to engine efficiency and energy savings.

Robust additive technology provides long-term benefits including reduced wear on critical valve-train components, including camshafts and hydraulic cam-followers and maintains a high level of engine cleanliness.

Multivis ECO V 0W-30 has the following benefits:

1. Increased engine efficiency, output and fuel economy.
2. Rapid cold start flow that reduces noise and wear.
3. Increased film strength at high temperatures under all driving conditions.
4. High temperature deposit and anti-sludge control.
5. Low levels of volatility.

### Applications

Multivis ECO V 0W-30 is recommended for petrol and diesel engines, including turbo-charged versions, requiring a low viscosity 0W-30 specifying one of the performance levels shown below:

### Performance Levels

API SL

ACEA A5/B5

Volvo 95200377

### Physical Characteristics

Viscosity @ 100°C, cSt.	10.26
Viscosity @ 40 °C, cSt.	56.15
Viscosity Index	174
Density @ 15.6°C	0.860
Flash Point (Closed) °C	230
TBN, mg/KOH/g	10.4
Pour Point, °C	-51

Figures based on average production values.

Part No.s: MZT001, MZT005 MZT025, MZT205

(TDS Multivis ECO V 0W-30 – 240622 Issue 3)

