



SAFETY DATA SHEET

Brake Fluid DOT 4

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Brake Fluid DOT 4
Product number 7833
Internal identification GHS22004

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Hydraulic fluid for use in automotive brake and clutch systems

1.3. Details of the supplier of the safety data sheet

Supplier Morris Lubricants
 Castle Foregate
 Shrewsbury
 SY1 2EL

08.45 - 17.00 GMT
 T: (+44)(0)1743 232200
 F: (+44)(0)1743 353584
 sds@morris-lubricants.co.uk

1.4. Emergency telephone number

Emergency telephone +44 (0)1743 232200 (08.45 - 17.00 hrs GMT)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture


Classification

Physical hazards Not Classified
Health hazards Eye Irrit. 2 - H319 STOT RE 2 - H373
Environmental hazards Not Classified

Classification (67/548/EEC or 1999/45/EC) Xi;R36.

2.2. Label elements

Pictogram



Signal word Warning

Hazard statements H319 Causes serious eye irritation.
 H373 May cause damage to organs through prolonged or repeated exposure if swallowed.

Brake Fluid DOT 4

Precautionary statements	P260 Do not breathe vapour/spray.
	P264 Wash contaminated skin thoroughly after handling.
	P280 Wear protective gloves/protective clothing/eye protection/face protection.
	P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P314 Get medical advice/attention if you feel unwell.
	P337+P313 If eye irritation persists: Get medical advice/attention.
Contains	P501 Dispose of contents/container in accordance with national regulations.

Contains 2-[2-(2-BUTOXYETHOXY)ETHOXY]ETHANOL, 2,2'-OXYBISETHANOL, 2-(2-butoxyethoxy)ethanol

2.3. Other hazards

Product is not classed as flammable or combustible but will burn.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

2-[2-(2-BUTOXYETHOXY)ETHOXY]ETHANOL 30-60%		
CAS number: 143-22-6	EC number: 205-592-6	REACH registration number: 01-2119531322-53-0000
Classification Eye Dam. 1 - H318	Classification (67/548/EEC or 1999/45/EC) Xi;R41	
2,2'-OXYBISETHANOL 10-30%		
CAS number: 111-46-6	EC number: 203-872-2	REACH registration number: 01-2119457857-21-0000
Classification Acute Tox. 4 - H302 STOT RE 2 - H373	Classification (67/548/EEC or 1999/45/EC) Xn;R22	
2-(2-METHOXYETHOXY)ETHANOL 1-5%		
CAS number: 111-77-3	EC number: 203-906-6	REACH registration number: 01-2119475100-52-0000
Classification Repr. 2 - H361d	Classification (67/548/EEC or 1999/45/EC) Repr. Cat. 3;R63	
2-(2-butoxyethoxy)ethanol 1-5%		
CAS number: 112-34-5	EC number: 203-961-6	REACH registration number: 01-2119475104-44-0000
Classification Eye Irrit. 2 - H319	Classification (67/548/EEC or 1999/45/EC) Xi;R36.	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments Blend of polyglycol ethers, glycol ether esters and polyglycols with added corrosion and oxidation inhibitors.

SECTION 4: First aid measures

Brake Fluid DOT 4

4.1. Description of first aid measures

General information	First aid personnel should wear appropriate protective equipment during any rescue.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
Ingestion	Get medical attention immediately. If patient is conscious, wash out mouth with water and give plenty of water to drink. If medical attention is delayed and an adult has swallowed several ounces, give 90-120ml of hard liquor such as 40%v/v spirits. For children give proportionally less at a rate of 2ml/kg bodyweight. Never give anything by mouth to an unconscious person. Do not induce vomiting unless under the direction of medical personnel.
Skin contact	Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.
Eye contact	Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyelids widely. If irritation persists: Seek medical attention and bring along these instructions.

4.2. Most important symptoms and effects, both acute and delayed

General information	See Section 11 for additional information on health hazards.
----------------------------	--

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Medical personnel seeking to administer first aid are referred to the services of the Poisons Information Service who can advise in such instances. There is no specific antidote and treatment of over exposure should be directed at control of symptoms and the patient's clinical condition. Due to the diethylene glycol content this material may have a mechanism of intoxication similar to ethylene glycol and treatment similar to that for ethylene glycol poisoning may help.
-----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	No special risk - combustion products may contain harmful or irritant fumes. Containers can burst violently or explode when heated, due to excessive pressure build-up.
-------------------------	---

5.3. Advice for firefighters

Protective actions during firefighting	Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Keep unnecessary and unprotected personnel away from the spillage. Avoid contact with skin, eyes and clothing. Take care as floors and other surfaces may become slippery. Wear protective clothing as described in Section 8 of this safety data sheet.
-----------------------------	--

6.2. Environmental precautions

Brake Fluid DOT 4

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Contain spillage with sand, earth or other suitable non-combustible material. Small Spillages: Wipe up with an absorbent cloth and dispose of waste safely. Collect and dispose of spillage as indicated in Section 13. Flush contaminated area with plenty of water.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid the formation of mists.

Advice on general occupational hygiene Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Suitable bulk storage vessels are mild/stainless steel tanks fitted with a dry air breathing system or tight head steel drums. Do not store in lined tanks or drums. Brake fluid absorbs water from the atmosphere - always keep containers tightly closed. Avoid contamination with any other substances and in particular with mineral oils which are incompatible.

7.3. Specific end use(s)

Specific end use(s) Users are referred to the Specification SAE J1701 'Service Maintenance of Brake Fluids'

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

2,2'-OXYBISETHANOL

Long-term exposure limit (8-hour TWA): WEL 23 ppm 101 mg/m³

Short-term exposure limit (15-minute): WEL

2-(2-METHOXYETHOXY)ETHANOL

8 hrs TWA 10ppm; 15 mins 50.1 mg/m³

2-(2-butoxyethoxy)ethanol

Long-term exposure limit (8-hour TWA): WEL 10 ppm 67.5 mg/m³

Short-term exposure limit (15-minute): WEL 15 ppm 101.2 mg/m³

WEL = Workplace Exposure Limit

2-[2-(2-BUTOXYETHOXY)ETHOXY]ETHANOL (CAS: 143-22-6)

DNEL

Workers - Dermal; Long term systemic effects: 50 mg/kg/day

Workers - Inhalation; Long term systemic effects: 195 mg/m³

Consumer - Dermal; Long term systemic effects: 25 mg/kg/day

Consumer - Inhalation; Long term systemic effects: 117 mg/m³

Consumer - Oral; Long term systemic effects: 2.5 mg/kg/day

Brake Fluid DOT 4

- PNEC**
- Water, Fresh water; 1.5 mg/l
 - Water, Marine water; 0.25 mg/l
 - Water, Intermittent release; 50 mg/l
 - STP; 200 mg/l
 - Sediment (Freshwater); 5.77 mg/kg/sediment dw
 - Sediment (Marinewater); 0.13 mg/kg/sediment dw
 - Soil; 0.45 mg/kg
 - Oral - ; 111 mg/kg

2,2'-OXYBISETHANOL (CAS: 111-46-6)

- DNEL**
- Workers - Dermal; Long term systemic effects: 106 mg/kg/day
 - Workers - Inhalation; Long term systemic effects: 60 mg/m³
 - Consumer - Dermal; Long term systemic effects: 53 mg/kg/day
 - Consumer - Inhalation; Long term systemic effects: 12 mg/m³

- PNEC**
- Water, Fresh water; 10 mg/l
 - Water, Marine water; 1 mg/l
 - Water, Intermittent release; 10 mg/l
 - STP; 199.5 mg/l
 - Sediment (Freshwater); 20.9 mg/kg/sediment dw
 - Soil; 1.53 mg/kg

2-(2-butoxyethoxy)ethanol (CAS: 112-34-5)

- DNEL**
- Workers - Inhalation; Short term local effects: 101.2 mg/m³
 - Workers - Dermal; Long term systemic effects: 20 mg/kg/day
 - Workers - Inhalation; Long term systemic effects: 67 mg/m³
 - Consumer - Inhalation; Short term local effects: 50.6 mg/m³
 - Consumer - Dermal; Long term systemic effects: 10 mg/kg/day
 - Consumer - Inhalation; Long term systemic effects: 34 mg/m³
 - Consumer - Oral; Long term systemic effects: 1.25 mg/kg/day

- PNEC**
- Water, Fresh water; 1.0 mg/l
 - Water, Marine water; 0.1 mg/l
 - Water, Intermittent release; 3.9 mg/l
 - STP; 200 mg/l
 - Sediment (Freshwater); 4.0 mg/kg/sediment dw
 - Sediment (Marinewater); 0.4 mg/kg/sediment dw
 - Soil; 0.4 mg/kg

2-(2-METHOXYETHOXY)ETHANOL (CAS: 111-77-3)

- DNEL**
- Workers - Dermal; Long term systemic effects: 0.53 mg/kg/day
 - Workers - Inhalation; Long term systemic effects: 50.1 mg/m³
 - Consumer - Dermal; Long term systemic effects: 0.27 mg/kg/day
 - Consumer - Inhalation; Long term systemic effects: 25 mg/m³

- PNEC**
- Water, Fresh water; 12 mg/l
 - Water, Marine water; 1.2 mg/l
 - Water, Intermittent release; 12 mg/l
 - STP; 10000 mg/l
 - Sediment (Freshwater); 44.4 mg/kg/sediment dw
 - Sediment (Marinewater); 0.44 mg/kg/sediment dw
 - Soil; 2.44 mg/kg

Brake Fluid DOT 4

8.2. Exposure controls

Appropriate engineering controls	Not necessary under normal conditions. If fluid is being heated or atomised, local exhaust ventilation with filter/scrubber is recommended.
Eye/face protection	Personal protective equipment for eye and face protection should comply with European Standard EN166. Provide eyewash station.
Hand protection	To protect hands from chemicals, gloves should comply with European Standard EN374. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. The selected gloves should have a breakthrough time of at least 8 hours.
Other skin and body protection	Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.
Hygiene measures	Good personal hygiene procedures should be implemented.
Respiratory protection	Not necessary under normal conditions.
Environmental exposure controls	Keep container tightly sealed when not in use.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Clear liquid.
pH	7.0 to 11.50
Melting point	<-50°C
Initial boiling point and range	>250°C @
Flash point	> 93°C PMCC (Pensky-Martens closed cup).
Vapour pressure	<2 mbar @ 20°C
Relative density	1.010-1.060 @ 20°C
Solubility(ies)	Miscible with water. Miscible with the following materials: Ethanol.
Partition coefficient	: < 2
Auto-ignition temperature	>300°C
Decomposition Temperature	>300°C
Viscosity	5-10 cSt @ 20°C
Explosive properties	Not considered to be explosive.
Oxidising properties	Does not meet the criteria for classification as oxidising.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Brake Fluid DOT 4

Possibility of hazardous reactions Glycol Ethers can form peroxides on storage. Glycol Ethers can react with light metals with the evolution of hydrogen.

10.4. Conditions to avoid

Conditions to avoid Do not distil to dryness without testing for peroxide formation.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents. For user safety, brake fluid should never be contaminated with any other substance.

10.6. Hazardous decomposition products

Hazardous decomposition products None known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,000.0

Species Rat

Notes (oral LD₅₀) Product is of low acute oral toxicity. However, if any significant amount is ingested, there is a risk of renal damage which in extreme cases could lead to kidney failure, coma or death. Other symptoms of overexposure include Central Nervous System effects, abdominal discomfort, metabolic acidosis, headache and nausea.

ATE oral (mg/kg) 5,000.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 3,000.0

Species Rabbit

Notes (dermal LD₅₀) Acute percutaneous toxicity is low however massive contact with damaged skin could result in the absorption of harmful amounts.

ATE dermal (mg/kg) 3,000.0

Acute toxicity - inhalation

Notes (inhalation LC₅₀) The product is unlikely to present any significant inhalation hazard at ambient temperatures and under normal conditions of use.

Skin corrosion/irritation

Human skin model test Based on available data the classification criteria are not met. Repeated contact may de-fat the skin and cause dermatitis.

Serious eye damage/irritation

Serious eye damage/irritation Serious eye irritation

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Brake Fluid DOT 4

Genotoxicity - in vitro	Based on available data the classification criteria are not met.
Genotoxicity - in vivo	Based on available data the classification criteria are not met.
<u>Carcinogenicity</u>	
Carcinogenicity	Based on available data the classification criteria are not met.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Major ingredients have not been shown to cause significant fertility or development problems at levels which are not themselves toxic to the animal concerned.
Reproductive toxicity - development	One minor ingredient - methyl diglycol - has been shown to affect foetus development in some studies and is classified as H631d.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	There are no reports of long term adverse effects in man. For one ingredient - diethylene glycol - human STOT effects on the kidney and gastrointestinal tract have been reported.
<u>Aspiration hazard</u>	
Aspiration hazard	Not anticipated to present an aspiration hazard, based on chemical structure.

SECTION 12: Ecological Information

12.1. Toxicity

Acute toxicity - fish	LC ₅₀ , 96 hours: >100 mg/l, Onchorhynchus mykiss (Rainbow trout)
Acute toxicity - aquatic invertebrates	Not determined but expected to be virtually non toxic.
Acute toxicity - microorganisms	Not determined but expected to be virtually non toxic.

12.2. Persistence and degradability

Persistence and degradability	Product is inherently biodegradable and is expected to be readily biodegradable based on ingredients.
Biodegradation	Water and sediment - Degradation 100%: 21 days

12.3. Bioaccumulative potential

Bioaccumulative potential	The product is not bioaccumulating.
Partition coefficient	: < 2

12.4. Mobility in soil

Mobility	The product is soluble in water. Soluble in water and will partition to aqueous phase. Volatilisation from water to air not expected. Mobile in soil until degraded.
-----------------	--

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	This substance is not classified as PBT or vPvB according to current EU criteria.
---	---

12.6. Other adverse effects

Other adverse effects	Not relevant.
------------------------------	---------------

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
----------------------------	---

Brake Fluid DOT 4

Disposal methods Controlled incineration or recycling is recommended. Do not dispose of to landfill or drains. It is recommended that contaminated packaging is either incinerated or cleaned and sent for recycling.

Waste class European Waste Catalogue (EWC) number: 16.01.13

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Water hazard classification WGK 1

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Inventories

EU - EINECS/ELINCS

All the ingredients are listed or exempt.

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

Australia - AICS

All the ingredients are listed or exempt.

Japan - MITI

Brake Fluid DOT 4

All the ingredients are listed or exempt.

Korea - KECI

All the ingredients are listed or exempt.

China - IECSC

All the ingredients are listed or exempt.

Philippines – PICCS

All the ingredients are listed or exempt.

New Zealand - NZIOC

All the ingredients are listed or exempt.

SECTION 16: Other information

Revision date 04/11/2015

Revision 1

Supersedes date 13/12/2012

SDS number 22004

Risk phrases in full R22 Harmful if swallowed.
R36 Irritating to eyes.
R41 Risk of serious damage to eyes.
R63 Possible risk of harm to the unborn child.

Hazard statements in full H302 Harmful if swallowed.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H361d Suspected of damaging the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure if swallowed.
H373 May cause damage to organs (Kidneys) through prolonged or repeated exposure if swallowed.